



## INNOVATION-EXCELLENCE-TRUST

# UNIT SIGNAL INC

E-mail: sales@unitsignal.com Add : NO.655, Xueshi Road, Shounan Subdistrict, Yinzhou Area, Ningbo City, Zhejiang, China

www.unitsignal.com

PRODUCT GUIDE 2021

# UNIT SIGNAL INC



# **UNIT SIGNAL**

INNOVATION Products engineered with purpose, built to last, and innovated with a forward vision

EXCELLENCE

and long lasting life

TRUST Products that you know you can trust and rely on



All products are built with materials of the highest quality in order to ensure performance with extreme durability



UNIT SIGNAL INC

UNIT SIGNAL was established in 2014. We are the manufacturer of Public Safety Warning Products and Systems for emergency services for nearly 10 years. We specialize in exterior and interior light bars, grille strobe lights, dash lights, traffic advisors, surface mounts, hideaways, beacons, and other accessories.

With a unique combination of innovation and design capabilities, it has developed rapidly in the past few years and has become one of the fastest-growing companies in the industry. We believe that the first responders should have the best products and the best technology to ensure the safety of workers, first responders, and our community. They are also the purpose of our progress! First responders need high-quality, reliable products that can withstand any environment and that any department can afford.

From the beginning, UNIT SIGNAL has focused your first choice in the market.



From the beginning, UNIT SIGNAL has focused on providing the best solution at the best price. We strive to make UNIT SIGNAL





## Grille & Surface Mounts

NEW	СТ608
NEW	NT609
	EG611
	N314
	N615
	KL616
	B417
	M3 M4 M618
	Z1219

## LightBars & Minibars

...28

...29

.30

...31

Matrix.....22

Mavic.....24

Maxus......26

Maxus mini.....32

ET30.....

ET60.....

Mistra.....

Matrix mini.....

## Dash & Deck & Visor

NEW	DE634
	VX1035
	DX337
	DX637

	Traffic Advisors		Beacons	
	TD-839	NEW	TB1846	
	TA-series40		LF1847	
	LA-series41		Spark48	
			SF-series49	
1	Hideaway Light		AR2450	
NEW	DA843			
	U120044			

PC8	52
PC16	53
PL16	54
PC44	55
PC134	56
Halo30	57
D3	58

## Perimeter Lights Sirens & Speakers

CJB-100CD60
CJB-100AD61
CJB-100RD62
CJB-2000163
SK0264
SK3C65
SK0366
Others67

Vertical **Grille & Surface** Horizontal Version Mounts





10-30V Voltage **Flash Patterns** 

20

CT6

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications	
10-30V	6PCS 3W 12PCS 3W	18W	20 25	single dual	Surface mount	/	30

Color:


# $\bigcirc$



## Features:

- Brand new CT6 light with Vertical or Horizontal Version
- Powered by DC 10 -30V
- Single color or Dual color available
- 6 Pcs or 12Pcs 3W LED with thin(12mm) design
- Aluminum base for efficient heat dissipation,UV-resistant PC
- With gas-permeable membrane to disperse water vapor
- 50% power steady on functions available
- Built-in 20(single color)/25(dual color) selectable
- flash patterns with Pattern Memory
- Simultaneously or alternately between multiple units
- IP-67 Standard, Weatherproof
- Fully encapsulated for moisture, vibration and corrosion resistance
- Long life LEDs rated to 100,000 hours of reliable operation

## Dimension:





**IP67** Waterproof





10-30 Voltage

12


**IP67** Flash Patterns



Color:  $\mathbf{O} \bullet \bullet \bullet$ 

## Features:

- Brand new NT6 light
- Powered by DC 10 -30V
- Single color or Dual color available
- Default with surface mount brackets and L-mount brackets
- 6 Pcs or 12Pcs 3W LED with width(15.8mm) design
- Aluminum base for efficient heat dissipation
- UV-resistant PC
- With gas-permeable membrane to disperse water vapor
- 50% power steady on functions available
- Built-in 12 selectable flash patterns with Pattern Memory
- Simultaneously or alternately between multiple units
- IP-67 Standard, Weatherproof
- Fully encapsulated for moisture
- Vibration and corrosion resistance
- Long life LEDs rated to 100,000 hours of reliable operation



Certifications





NT6

Voltage	LED Power
10-30V	6PCS 3W 12PCS 3W

18W

12

Flash Pattern

Colour

single dual

Max Power

surface mount, L-bracket

Mount

09













10-33 Voltage

12 Flash Patterns

**IP67** 

Waterproof


Flash Pattern



## Features:

- Powered by DC 10 -33V
- 6 Pcs or 12Pcs 3W LEDs with new super thin(7mm) design
- Single color or Dual color available
- Surface mount or 3M mount or L-bracket mount
- or hood mount for optional choice
- Plastic of Optics lens from Degussa(GER)
- and LED Driver from MPS(UK)
- Extra steady on functions for vehicle identification or illumination.
- Built-in 12 selectable flash patterns with Pattern Memory
- Simultaneously or alternately between multiple units
- Aluminum base for efficient heat dissipation
- IP-67 Standard, Weatherproof
- Long life LEDs rated to 100,000 hours of reliable operation
- Reverse polarity protection

### Dimension:









Voltage	LED Power	Max Power
10-33V	3W LEDs	18W

Colour Mount Surface mount single dual 3M mount L-bracket mount hood mount

Certifications ECE R65 XA2&XB2 and SAE

11







Surface Mounts LightBars

UNIT SIGNAL INC

17

LED Power

3PCS 3W 6PCS 3W

Flash Patterns

Voltage

10-33V

10-33

Voltage


Flash Pattern Max Power 9W 17 18W



**IP68** Waterproof

Colour

single dual







Surface Mounts LightBars

UNIT SIGNAL INC









19 Flash Patterns with Pattern Memory
180° light spread model
Single color, Split color, Dual color available
<ul> <li>Synchronize to other unit signal sync products</li> </ul>
<ul> <li>IP-68 Standard; a gas-permeable membrane</li> </ul>
to disperse water vapor - suitable for high altitude use
<ul> <li>Weatherproof ready for exterior mounting.</li> </ul>
Aluminum alloy base,UV-resistant PC, Multifunctional wire
<ul> <li>Perfect for mounting anywhere on your vehicle</li> </ul>
Lifespan of up to 100,000 hours

10-33 Voltage

19 Flash Patterns

**IP68** 

Waterproof

20.5MM


Color:

Features:

Powered by 10-33V

High intensity LED

 $\bigcirc$ 



N	6
---	---

	Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications			Voltage
16	10-33V	6PCS 3W 12PCS 3W	18W 36W	19	single dual	Surface mount		15	KL6	10-30V 6

Dimension:





10-33 Voltage

B

19 Flash Patterns

**IP68** 

Waterproof



## Features:

- We use 6 LEDs in the single color verson to make the light brighter.
- Aluminum alloy base,Lens PMMA, Multifunctional wire
- Powered by 10-33V
- High intensity LED; Single or dual color are available
- Flash Patterns with Pattern Memory (watch the video)
- 180° light spread model
- Synchronize to other unit signal sync products
- IP-68 Standard; a gas-permeable membrane to disperse
- water vapor suitable for high altitude use
- Perfect for mounting on the grille, bumper,
- or dash of an emergency vehicle
- Lifespan of up to 100,000 hours

## Dimension:





Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers



12-24 16 Voltage Flash Patterns

**IP67** Waterproof

Colour

single

Surface mount

<b>34</b>	Voltage 10-33V	 	 	Mount  Surface mount	 17	M-series	M3 M4 M6	Voltage 12-24V	Max Power 9W 12W 18W	

18



<ul> <li>Powered by 12-24V</li> <li>4 high intensity LED with optic lenses</li> <li>16 Flash Patterns with Pattern Memory (single color / s</li> </ul>	
<ul> <li>16 Flash Patterns with Pattern Memory (single color / s</li> </ul>	
	plit col
<ul> <li>Synchronization between multiple units</li> </ul>	
Compactly sized for versatile application	
Built in heat sink	
<ul> <li>Black flange included for protection and stealth</li> </ul>	
Virtually Out of Sight	
Extremely Bright—Highly Visible when ON!	
IP-67 Standard	
<ul> <li>Weatherproof ready for exterior mounting. (Not subme</li> </ul>	rsible)
Lifespan of up to 100,000 hours	
Meets or Exceeds SAE J595 Standards	





12-24 Voltage 16 Flash Patterns


IP67 s Waterproof



## Features:

- Powered by 12-24V
- 12Pcs 3W high intensity LED
- 16 Flash Patterns with Pattern Memory
- Synchronization between multiple units
- Low-profile thickness, Compactly sized for versatile application
- Heavy-duty aluminium housing
- IP-67 Standard
- Weatherproof and vibration resistant design
- Black flange included for protection and stealth
- Lifespan of up to 100,000 hours
- Meets or Exceeds ECE R65 Standards

## Dimension:





# LightBars & Minibars







# Matrix Lightbar

The Matrix lightbar is the first Trio-color LED warning lightbar on the market today, and offers universal gutter brackets and controller.



Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights UNIT SIGNAL INC



10-30 Voltage


15 Flash Patterns


**IP67** Waterproof

ash Pattern

Matrix

Voltage	LED Power	Max Power	FI
10-30V	3W LEDs		1:





Mavic Lightbar

The Mavic LED Full Size Light Bar features 1-watt or 3-watt high intensity Super bright LEDs with built-in ultra bright take downs and alleys. Universal gutter brackets and controller included for easy installation & use.



Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights




UNIT SIGNAL INC

16

10-30 Voltage Flash Patterns **IP67** 

Voltage LED Power Max Power 10-30V 135 PCS 3W



Flash Pattern	Colour	Mount	Certifications
16	RBAW	Magnet mount Gutter Mount	ECE R65 TB1 ECE R65 TA1 ECE R10



	Surface Mounts	LightBars	Da
UNIT SIGNAL INC			-



# Maxus Lightbar

Red/Blue/Black/Clear/Amber lens available for the Maxus lightbar. Choose from Single or Dual or Trio-color version.



12-24 Voltage

Maxus

15 Flash Patterns

Waterproof

Voltage	LED Power	Max Power	Fla
12-24V	3W LEDs		15









UNIT SIGNAL INC

The 12inch ET30 LED Mini Light Bar is a compact lightbar designed with 30pcs 3-watt LEDs and 12 available flash patterns.



rface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers





12


Flash Patterns

12-30 Voltage

**IP67** 

	_
Т	3(
	Т

Voltage	LED Power	Max Power	
12-30V	30PCS 3W	90W	



Waterproof



Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers



12-30 Voltage

Ξ

# 12 Flash Patterns

**IP67** Waterproof




## Features:

- Powered by 12-30V
- 60Pcs 3-Watt LEDs
- 12 Flash Patterns with Pattern Memory
- Lifespan of up to 100,000 hours
- 360°High-Intensity Illumination
- Includes 2.8m of cable from light bar to cigarette plug
- Weather-proof housing
- Includes Magnetic-Mounting or screw, Easy Installation
- Robust and Solid








12-30 Voltage

UNIT SIGNAL INC

15 **Flash Patterns** 

**IP67** Waterproof

	Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications			Voltag	je	LED Power	Max Power	Flash Patt
T60	12-30V	60PCS 3W	180W	12	single and split	Magnet mount Screw mount		29	Mistra	12-30	V	3W LEDs		15







10-30 15 Voltage Flash Patterns






Color:  $\mathbf{O}$ 

## Features:

- Single or Dual color available
- Powered by 10-30V
- High intensity 1W or 3W Super bright LED
- Magent mount
- Feet covered with rubber protector
- 15 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- IP67 Waterproof Exterior Light bar
- Includes 4m of cable with controller provided
- Optional controller for purchase
- Meets or Exceeds ECE R65 TA1, ECE R65 TB1, ECE R10

## Dimension:





12-24 Voltage


UNIT SIGNAL INC

15 **Flash Patterns** 

**IP67** Waterproof

tter

Matrix mini	Voltage 10-30V	LED Power 40PCS 3W	Max Power 120W		Mount ——— Magent mount	Certifications ECE R65 TA1 ECE R65 TB1 ECE R10	31	Maxus mini	Voltag 12-24	 LED Power 56PCS 3W	Max Power 168W	Flash Pat  15





UNIT SIGNAL INC

Dash & Deck

& Visor





10-33 Voltage

20or16 Flash Patterns

IP67 Waterproof

F6	

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications	
DC 10-33V	3W LEDs	18W	20 or 16	single dual trio	3M mount Velcro mount	ECE R65 and SAE	34

Color: Features: DE6 dash light uses the EG6 modules and accessories. It can be easily mounted to vehicle's Front/Rear windshield. Compliant with ECE R65 and SAE certificated Powered by DC 10 -33V 6 Pcs or 12Pcs or 18Pcs 3W LEDs Single color or Dual color or Trio color available Built-in 20 selectable flash patterns for single color version 16 for dual and Trio color version Pattern Memory available Simultaneously or alternately between multiple units IP-67 Standard, Weatherproof Long life LEDs rated to 100,000 hours of reliable operation Reverse polarity protection





Voltage

Flash Patterns Waterproof



## Features:

- Powered by 12V
- Single or Split or Dual color available
- 60Pcs GENIII 3-Watt LEDs
- (30) 3-Watt Colored LEDs (30) 3-Watt Takedown LEDs
- 41 flash patterns
- Default cigar plug with on/off & flash pattern
- Flash pattern memory
- Sleek, durable housing
- Includes universal brackets

## Included in the Box:

- VX10 visor light bar
- Default cigar plug
- Universal visor mount brackets
- 3m of cable with cigarette plug provided
- Half: 450mm L x 105mm W x 30mm H

VX1	0

Voltage	LED Power
12V	30PCS 3W 60PCS 3W

90W

Max Power

Flash Pattern

11 41 single or split dual Brackets mount

Mount

Colour

Certifications

35



# VX10 LED Visor Light

## Dual Color available

## 60Pcs 3-Watt LEDs

## Universal mount brackets

261

F. C. M



DX3 DX6



12 17 Voltage Flash Patterns W

Waterproof



# Voltage LED Power Max Power Flash Pattern Colour Mount Certifications 12V 6PCS 3W 9W 17 dual Suction cup / 37

Color:

## Features:

- Dual color dash lights
- Powered by 12V
- 3PCS 3-watt high intensity LED
- 17 Flash Patterns with Pattern Memory
- 4 suction cups for stabilized mounting
- Synchronization between multiple units
- Lifespan of up to 100,000 hours
- Cigarette plug with On/Off switch and flash pattern changer
- DX3: 115mm L x 100mm W x 60mm H
- DX6: 200mmL \* 100mmW \* 60mmH

# Traffic Advisors

1911911911





UNIT SIGNAL INC





10-30 Voltage

59 Flash Patterns

**IP67** Waterproof



1220/1500/1800\*45\*41mm

Rugged Aluminum Housing

Color: () () ()

Powered by DC 10-30V

and can be dimmed by 50%

(96) 3 Watt LEDs with TIR lens

Features:



Features dual color mode with super bright Takedown

ight when opening your door for additional visibility

Sleek and low-profile with a high light intensity

Includes Brackets, additional screws and 4m cable

59 Flash Patterns with Pattern Memory

Waterproof for Exterior Mounting

Lifespan of up to 100,000 hours

The flood option allows you to use the light as a courtesy I

12-24 Voltage

19 Flash Patterns

Waterproof

D-8	Voltage 10-30V	LED Power 96PCS 3W	Max Power 144W	Flash Pattern  59		Mount lor bracket mount	Certifications /	39	TA-2 TA-4 TA-6 TA-8	Voltage  12-24V	LED Power 8PCS 3W 16PCS 3W 24PCS 3W 32PCS 3W	Max Power 24W 48W 72W 96W	Flas
					lakeuowii								

40

Color:  $\mathbf{O}$ Features: Powered by 12VDC or 12-24VDC TIR or LIN lens are available (8) 3 Watt Generation IV LEDs 16 Flash Patterns with Pattern Memory 3 Selectable directional flash patterns Powerful, Compact Light Bar/ Sleek, durable casing Waterproof for Exterior Mounting, IP67 Lifespan of up to 100,000 hours Includes Brackets and 10ft cable Optional cigarette plug with on/off & flash pattern controls Optional Controller Box available for purchase Dimension: 250/490/730/970mm L x 65mm W x 46.5mm H



**IP67** 





12-24 Voltage 16

IP67 s Waterproof

Flash Patterns



## Features:

- Powered by 12VDC or 12-24VDC
- TIR or LIN lens are available
- (8) 3 Watt Generation IV LEDs
- 16 Flash Patterns with Pattern Memory
- 3 Selectable directional flash patterns
- Powerful, Compact Light Bar/ Sleek, durable casing
- Waterproof for Exterior Mounting, IP67
- Lifespan of up to 100,000 hours
- Includes Brackets and 10ft cable
- Optional cigarette plug with on/off & flash pattern controls
- Optional Controller Box available for purchase


## Dimension:

250/490/730/970/120.5mm L x 65mm W x 46.5mm H

41

# Hideaway Light

Voltage LED Power Max Power Flash Pattern Colour Mount Certifications LA-series LA-2 LA-4 LA-6 LA-8 12-24V 36W 72W 108W 144W 12PCS 3W 24PCS 3W 16 Single and dual Brackets mount 36PCS 3W 48 PCS 3W



UNIT SIGNAL INC





UNIT SIGNAL INC



10-33

Voltage

12 Flash Patterns

**IP67** Waterproof Color:  $\mathbf{O}$ 

### Features:

- Powered by 10-33V
- 8Pcs 3-watt high intensity LEDs
- Single color or Dual color available
- 12 Flash Patterns with Pattern Memory
- Plastic of Optics lens from Degussa(GER) and LED Driver from MPS(UK)
- New design of Aluminum base increase heat dissipation
- Easy to install for surface or internal mount within head light, tail light
- Lifespan of up to 100,000 hours

Dimension:

Easily replaces traditional hideaway strobe with existing 1" hole

Certifications



U1200 U1200 eco

# 19

**IP67** Flash Patterns

55 46 00 0,	

DA8

Voltage	LED Power	Max Power
10-33V	8PCS 3W	24W

12

Flash Pattern

Colour

Mount single or dual Surface mount Internal mount

43

U1200

oltage	LED Power	Max Power
0-30V	12PCS 3W 8PCS 3W	36W 24W

Color:  $\bigcirc$ Features: Powered by 10-30V Each unit consists of 12Pcs 3-watt high intensity LEDs 19 Flash Patterns with Pattern Memory Good for surface or internal mount within head light, tail light, and various setups on personal emergency vehicles Lifespan of up to 100,000 hours 100% Waterproof Easily replaces traditional hideaway strobe with existing 1" hole Dimension: Certifications Mount Surface mount single or dual 44

Waterproof

Flash Pattern

19

Colour



UNIT SIGNAL INC



12 Voltage

**TB18** 

84 Flash Patterns

LED Power

18PCS 1W


Voltage

12V

Waterproof

Max Power

6W





IP67

Flash Pattern

84

Colour

single dual

trio

Mount

Certifications

Permanent mount / Magnet mount





### Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers



22 Available Flash Patterns(include rotation flash mode)

Features:

Powered by 10-30V

18Pcs high intensity GenIII LEDs

distributed on the nine surfaces

Optional Magnetic and Permanent mount

Amber/Red/Blue/Clear lens available

Lifespan of up to 100,000 hours

UV stabilized lens resists fading

IP67 waterproof designed

Luminous flux > 540lm

Dimension:

# 

Surface Mounts LightBars

UNIT SIGNAL INC







10-30 Voltage



**IP67** Waterproof

Flash Pattern

22

Colour

RBAW



Certifications



8 Flash Patterns

**IP67** Waterproof

	Ī

Voltage	LED Power	Max F
10-30V	18PCS 1W	18W

Permanent mount / Magnet mount

Mount

47



Voltage	LED Power	Max Power
10-30V	12PCS 1W	12W

Color: Features: Energy-saving beacon light Powered by 10-30V 12Pcs high intensity LEDs. Amber and Red lens available IP67 Double waterproof designed 8 Available Flash Patterns(including rotating) Max output of 0.52 Amps Optional Magnetic and Permanent mount 2.8m of cable with cigarette plug provided Lifespan of up to 100,000 hours UV stabilized lens resists fading, strong tooth structure and stylish design Dimension: • 0 80mm\*60mm\*165mmH

Certifications Flash Pattern Colour Mount Amber and Red Permanent mount Magnet mount

48

# Sur

## Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers






10-30 10 IP67 Voltage Flash Patterns Waterproof



- Lumin: 640LM
- Each unit consists of 16 high intensity LEDs.
- IP67 rated weather-proof housing.
- 10 Available Flash Patterns
- Max output of 2 Amps
- Optional Permanent mount
- Synchronization between multiple units
- Lifespan of up to 100,000 hoursUV-resistant PC
- Meets or Exceeds SAE J845 Standards

### Dimension:






UNIT SIGNAL INC


12 Flash Patterns IP67 Waterproof



Surface Mounts LightBars







ash Pattern	Colour	Mount	Certifications
2	Amber	Permanent mount Magnet mount	/





UNIT SIGNAL INC



12/24 18 Voltage **Flash Patterns** 

	Voltage	LED Power	Max P
PC8	12V or 24V	8PCS 3W	24W



**IP67** Waterproof





# 

## Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers



12/24 Voltage

## 18 Flash Patterns

**IP67** 


Waterproof



## Features:

- LED technology provides better lighting
- with far less amperage than halogen
- Voltage 12 or 24 VDC
- 16 High power 3-watt LEDs
- Available with up to 18 flash patterns
- Single Colors or Split Color available
- Amber, Red, Blue or Clear Lenses available
- Easy to Install or Retrofit
- Covered with rubber protector
- Weather and vibration resistant
- Sychronization between Multiple modules
- Includes chrome bezel














12/24 18 Flash Patterns Voltage

PC16	Voltage 12V or 24V	 	 	Mount Surface mount	 53	<b>PL16</b>		 	 Mount Surface mount	 5	4



**IP67** Waterproof



242MM



### Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers Surface Mounts LightBars



12/24 4 Voltage **Flash Patterns** 





## Features:

- Voltage 12 or 24 VDC
- 44 High power 0.5-watt LEDs
- Provides 180°light spread
- 4 selectable flash patterns
- Amber, Red, Blue or Clear Lenses available
- Easy to Install or Retrofit
- Weather and vibration resistant
- Covered with rubber protector
- Sychronization between Multiple modules
- Includes chrome bezel

Dimension:



UNIT SIGNAL INC



4

12/24 Voltage

**Flash Patterns** 

Max Power

67W




## Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers





**IP67** Waterproof





Flash Pattern

4

Colour A R B Clear

lens available

Mount

## Certifications

Surface mount

56

# Η UNIT SIGNAL INC

## Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers

Color:

Features:

0

4 Inch Round Chrome plated Tail Light

Flash function available

Powered by DC 12-24V 14Pcs+16Pcs 0.4W LEDs

Amber/Red/White lens available

Easy to install in all locations

Yellow: Flash; Black: GND)

Dimension:

IP67 Waterproof PC Lens, Shock Proof, Dust Proof

Truck and trailer LED lighting with STT(stop/turn/tail) functions

Test Each Item and 100% Ensure In Good Condition Before Shipped

5 wires(Red: Halo+Middle Part; Blue: Middle Part; White: Halo;







12-24 Voltage

Flash Patterns

**IP67** 

Waterproof




10-30 Voltage

**Flash Patterns** 

**IP67** Waterproof


	Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications			Voltage	LED Power	Max Power	Flash
lalo30	12-24V	30Pcs 0.4W	12W	/	A R W	Surface mount	/	57	D3	10-30V	3PCS 0.2W	0.6W	/





sh Pattern

Surface mount DOT SAE P2P3 20





UNIT SIGNAL INC



12/24 Voltage

120-130 8Ω/11Ω



Voltage	Sound	Max Power	0
12/24V	120-130dB	100W	2

Sound

Features:

- It conform to national standrad GB8108-1999.
- Special super-thin design, harmonious with inner decoration.
- Case is all metal PAINTED black enamel.
- Adjustable metal chrome plated swing bracket, provided.
- Novelty structure, attractive design, excellent,
- excellent performance, complete function, convenient operation.
- Monolithic Integrated circuit in steadier performance.
- Volume of amplifier tone and warning tone are adjusted are your option.
- With two light controllers.



Impedance

Accessories

Tone

8Ω/11Ω output group ach MAX 8A

Bracket.Fuse Wires

Siren, wail-2, tool, yelp, hi-lo, wail-1, horn 60

Impedance

# 

### Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers

### UNIT SIGNAL INC




12/24 Voltage

## 120-130 8Ω/11Ω Sound Impedance

## Features:

- Meet SAE J1849 and CA Title 13 requirements
- Handhold mike, with controller
- Monolithic integrated circuit in steadier performance
- With two lights controllers
- Dimensions: 7.6" L x 6.1" W x 3.8" H
- Tone: Siren, manual, wail, yelp, hi-lo, horn, radio
- Unique and scientific design, perfect function,
- convenience for operation, safely and reliably
- Design and produced in accordance with GB standard character
- 15 Amp fuse, Mounting Bracket, Wires

### Instruction:



## 12/24 Voltage

# 116-118 8Ω/11Ω

Sound

Cu	B	
-100		)

Voltage 12/24V	Sound 120-130dB	Max Power 100W	Output 2 output group Each MAX 8A	Impedance 8Ω/11Ω	Accessories Bracket Fuse Wires	Tone Siren,manual wail,yelp,hi-lo horn,radio	61	<b>CJB</b> -100RD	Voltage 12/24V	Sound  116-118dB	Max Power 100W	Output 3 output gr Each MAX






Impedance

### Features:

- Meet SAE J1849 and CA Title 13 requirements
- Handhold controller
- Monolithic integrated circuit in steadier performance
- Function: aux, yelp, hi-lo, wail-1, wail-2,
- siren, horn, super-siren, yelp relay, tool
- Dimensions: 7.8" L x 4.3" W x 1.9" H
- Tone: police, fire fighting, wrecker,
- project, ambulacne, guest siren
- Unique and scientific design, perfect function,
- convenience for operation, safely and reliably
- Design and produced in accordance with GB standard character
- Additional functions of two sets switched
- of light control in the panel
- Bulid in LED display, sound amplifying

### Instruction:



Impedance

group 4X 15A 8Ω/11Ω

Accessories

### Tone

Polic, fire fighting wrecker, project, ambulance, guest



# 

UNIT SIGNAL INC

### Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers

### Features:

- Meet GB 8108-1999 «electronic siren for vehicle»
- Remote controller
- Pretty appearance, advanced structure and complete function
- Dimensions: AMP: 225 x 108 x 51mm;
- Controller: 105 x 53 x 19mm
- Siren is exothermic, should be install at a ventilated palce
- Controller should be put at a place that easy for user
- to pick up and away from air bag restraint system







Sound

12V Voltage

120-130 8Ω/11Ω



10-14 Voltage



4Ω

impedance



Impedance



Voltage	Sound	Max Power	impedance
10-14V	120-130dB	200W	4Ω

Controller current	Shell color
12A X 3	Black

Current of lamp control

3 sets of lamp control 63



Voltage Sound Max Power 120-130dB 100W 12V

### Features:

- 100W speaker
- Black ABS plastic shell and High quality Aluminum alloy
- Dimensions: 18.8\*16.2\*8.7mm
- Set in one package : 6



mpedance	Frequency	Distortion	Dimensions	
Ω/11Ω	400-4000Hz	/	 18.8*16.2*8.7mm	



### Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights

Sirens & Speakers



UNIT SIGNAL INC



Sound

12V Voltage



Features: 100W speaker

- High quality Aluminum alloy
- Dimensions: 145\*125\*52mm
- Set in one package : 6



120-130 12V 8Ω/11Ω Sound Impedance Voltage





Max Power Sound Voltage 12V 120-130dB

Impedance 100W 8Ω/11Ω

Frequency Distortion 400-4000Hz

Dimensions 145\*125\*52mm

65



Voltage Sound Max Power 120-130dB 100W 12V

### Features:

- 100W speaker
- ABS plastic shell and High quality Aluminum alloy
- Set in one package : 6
- Impedance: 4/6/8/11ohm



Impedance





Speak

S802 80W Speaker

S2001 200W Speaker

UNIT SIGNAL INC





S30 30W Speaker



		Voltage	Sound	Max Power	Impedance	Frequency	Distortion	Dimensions				Voltage	Sound	Max Power	Impedance	Frequency	Distortion	Dimensions	
	S801	12V	120-130dB	80W	16Ω	400-4000Hz					S30	12V	120-130dB	30W	17Ω	400-4000Hz			
ker	S802	12V	120-130dB	80W	16Ω	400-4000Hz				Speaker	C12	12V	115-122dB	100W	8Ω/11Ω	400-4000Hz			
ker	S2001	12V	120-130dB	200W	4Ω	400-4000Hz				Speaker	B12	12V	115-122dB	100W	8Ω/11Ω	400-4000Hz			
	S2002	12V	120-130dB	200W	4Ω	400-4000Hz			67	-	A2	12V	120-130dB	100W	8Ω/11Ω	400-4000Hz			68
	S20012	12V	118-125dB	200W	4Ω	300-5000Hz													









C12 100W Speaker



# **SPECIFICATIONS**

Description











Item	CT6	EG6	N3	N6	KL6	B4
LED Power	6/12Pcs 3W LEDs	3W LEDs	3PCS 3W / 6PCS 3W	6PCS 3W	6PCS 3W	8PCS 3W
Lens	/	Fresnel	Fresnel lens	Fresnel lens	TIR	TIR
LED Lifespan	100000H	100000H	100000H	100000H	100000H	100000H
Flash pattern	20/25	12	17	19	16	19
Input voltage	10-33V	10-33V	10-33V	10-33V	10-30V	10-33V
Max Power	18W	18W	9W	18W	18W	12W
Colour Available	single and dual	single or dual	single or dual	single or dual	RWAB	single or dual
Ambient temperature	-30+70°C	-30+70°C	-30+70°C	-30+70°C	-30+70°C	-30+70°C
Waterproof	IP67	IP67	IP68	IP68	IP67	IP68
Product Dimension	105mm L x 28mm W x 12mm H	118mm L x 25mm W x 7mm H	108mm L x 36mm W x 18mm H	185mm L x 36mm W x 18mm H	108mm L x 27mm W x 22mm H	115mm L x 30.5mm V x 15.2mm H
Mounting	Surface mount	surface mount/L-bracke /3M/hood mount	<sup>t</sup> Surface mount	Surface mount	Hood mount	Surface mount
Certifications	/	/	/	/	/	/
Wire	4 core	5 core	4 core	4 core	4 core	4 core
Cable length	20cm	20cm	20cm	20cm	20cm	20cm
Material	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base Lens PMMA



M3	M4	M6	NT6	Z12	DX3	DX6
3PCS 3W	4PCS 3W	6PCS 3W	6/12PCS 3W	12PCS 3W	3PCS 3W	6PCS 3W
TIR	TIR	TIR	TIR	/	Fresnel lens	Fresnel lens
100000H	100000H	100000H	100000H	100000H	100000H	100000H
16	16	16	12	16	17	17
12-24V	12-24V	12-24V	10-30V	12-24V	12V	12V
9W	12W	18W	18W	36W	9W	18W
RWAGB	R W A G B and split color	R W A G B and split color	Single and Dual	RWAGB	R B A W G and dual color	R B A W G and dual color
-30+70°C	-30+70°C	-30+70°C	-30+70°C	-30+70°C	-30+70°C	-30+70°C
IP67	IP67	IP67	IP67	IP67	/	/
86.2mm L x 27.6mm W x 16.2mm H	96.1mm L x 27.6mm W x 16.2mm H	94.8mm L x 34.4mm W x 20.5mm H	120mmLx 22.2mmW x 15.8mm H	132.8mmLx45mmW x 10.2mm H	115mm L x 100mm W x 55mm H	200mmL x 100mmW x 60mmH
Surface mount	Surface mount	Surface mount	Surface mount/L-brackets	s Surface mount	Suction cup mount	Suction cup mount
/	/	/	/	ECE R65 XA1	/	/
5 core	5 core	5 core	4 core	1 pos, 1 Neg, 1 sync, 1 pattern,1 alt	/	/
20cm	20cm	20cm	20cm	20cm	2.5m of cable with cigarette plug provided	2.5m of cable with cigarette plug provided
Aluminum alloy base	Aluminum alloy base	Aluminum alloy base	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum housing Lens PMMA	Aluminum housing Lens PMMA

# **SPECIFICATIONS**

Description







Item	Maxus	Mistra	Mavic	Matrix
LED Power	3W LEDs	3W LEDs	3W LEDs	3W LEDs
Lens	Red/Blue/Black/Clear/Amber	Black/Silver-white	Blue/Clear/Amber/Black	Red/Blue/Clear/Amber/Black
LED Lifespan	100000H	100000H	100000H	100000H
Flash pattern	15	15	16	16
Input voltage	12-24V	10-30V	10-30V	10-30V
Max Power	/	/	/	/
Colour Available	single or dual or trio color	RWAGB	R W A G B	single or dual or trio color
Ambient temperatur	-30+70°C	-30+70°C	-30+70°C	-30+70°C
Waterproof	IP67	IP67	IP67	IP67
Product Dimension	900/1210/1515mm L x 305mm W x 155mm H	1200/1400mm L x 306mm W x 140mm H	(740-2090)mm L x 240mm W x 138mm H	(690-2050)mm L x 300mm W x 136mm H
Mounting	Magnet mount or Gutter Mount	Gutter mount or permanent mount	Magnet mount or Gutter Mount	Magnet mount or Gutter Mount
Certifications	/	/	ECE R65 TA1, TB1, ECE R10	ECE R65 TA1, TB1, ECE R10
Wire	/	/	/	/
Cable length	4m of cable with controller provided	4m of cable with controller provided	4m of cable with controller provided	4m of cable with controller provided
Material	UV-resistant PC	Aluminium and UV-resistant PC	UV-resistant PC	UV-resistant PC



Matrix mini	ET30	ET60	Maxus mini	TD-8
40pcs 3W	30PCS 3W	60PCS 3W	56PCS 3W	96PCS 3W
TIR	/	/	Red/Blue/Amber/Clear	TIR
100000H	100000H	100000H	100000H	100000H
15	12	12	15	59
10-30V	12-30V	12-30V	12-24V	10-30V
120W	90W	180W	168W	144
single or dual or trio color	R W A G B	R W A G B	R W A G B or combo color	single or split color with white color takedown
-30+70°C	-30+70°C	-30+70°C	-30+70°C	-30+70°C
IP67	IP67	IP67	IP67	IP67
590mm L x 300mm W x 136mm H	305mm L x 185mm W x 45mm H	440mm L x 220mm W x 45mm H	600mm L x 300mm W x 54mm H	1220/1500/1800mm L x 45mm W x 41mm H
Magnet mount	Magnet mount, Or Screw	Magnet mount,Or Screw	Magnet mount	Brackets mount
ECE R65 TA1, TB1, ECE R10	/	/	/	/
/	/	/	/	/
4m of cable with controller provided	2.8m of cable with cigarette plug provided	2.8m of cable with cigarette plug provided	4m of cable with cigarette plug provided	4m
UV-resistant PC	UV-resistant PC	UV-resistant PC	UV-resistant PC	Aluminum alloy base,UV-resistant PC



# **SPECIFICATIONS**

Description







Item	VX10	DA8	U1200	U1200 eco	PC8
LED Power	60PCS 3W	8PCS 3W	12PCS 3W	8PCS 3W	8PCS 3W
Lens	Fresnel lens	1	/	/	Amber/Red/Clear/Blue
LED Lifespan	100000H	100000H	100000H	100000H	100000H
Flash pattern	41	12	19	19	18
Input voltage	12V	10-33V	10-30V	10-30V	DC12V or DC24V
Max Power	90W	24W	36W	24W	24W
Colour Available	single or split or dual color	Single or dual color	Single or dual color	Single or dual color	Single color or split
Ambient temperature	-30+70°C	-30+70°C	-30+70°C	-30+70°C	/
Waterproof	/	IP67	IP67	IP67	IP67
Product Dimension	Half:450mm L x 105mm W x 30mm H	ø 55mm x 21.6mm H	ø 36mm x 20mm H	ø 36mm x 20mm H	201mm L x 94mm W x 40mm H
Mounting	Brackets mount	Surface mount or Internal mount	Surface mount	Surface mount	Surface mount
Certifications	/	1	/	/	/
Wire	/	4 core / 5 core	4 core	4 core	3 core
Cable length	3m of cable with cigarette plug provided	20CM	20CM	20CM	20cm
Material	Aluminum alloy	Aluminum alloy base UV-resistant PC			




PC16	PL16	PC44	PC134	Halo 30	D3
16PCS 3W	16PCS 3W	44PCS 0.5W	134PCS 0.5W	30PCS 0.4W	3PCS 0.2W
Amber/Red/Clear/Blue	Amber/Red/Clear/Blue	Amber/Red/Clear/Blue	Amber/Red/Clear/Blue	Amber/Red/White	Amber/Red/Clear/Blue
100000H	100000H	100000H	100000H	500000H	500000H
18	18	4	4	/	/
DC12V or DC24V	DC12V or DC24V	DC12V or DC24V	DC12V or DC24V	DC12-24V	DC10-30V
48W	48W	22W	67W	12W	0.6W
Single color or split	Single color or split	Single color	Single color	Single color	Single color
/	/	/	/	/	/
IP67	IP67	IP67	IP67	IP67	IP67
268mm L x 212mm W x 55mm H	242mm L x 184mm W x 50mm H	201mm L x 294mm W x 40mm H	268mm L x 212mm W x 55mm H	4 inch	3/4 inch
Surface mount	Surface mount	Surface mount	Surface mount	Surface mount	Surface mount
/	/	/	/	/	DOT SAE P2P3 20
3 core	3 core	3 core	3 core	5 core	2 core
20cm	20cm	20cm	20cm	20cm	20cm
Aluminum alloy base UV-resistant PC	UV-resistant PC	UV-resistant PC			









## + WHAT MAKES US UNIQUE

UNIT SIGNAL was established in 2014. We are the manufacturer of Public Safety Warning Products and Systems for emergency services. We believe that the first responders should have the best products and the best technology to ensure the safety of workers, first responders, and our community.

## + Design & Engineering

UNIT SIGNAL believes that the key to continued growth and success is through continuous product development, combined with excellent customer service, low delivery times, competitive prices, and product reliability. We can custom design and manufacture LED warning lights according to customer specifications and other requirements.

Electronics Manufacturing

One-stop electronic manufacturing: purchase of components, the supply of circuit substrates, design and application of built-in electronic equipment, manufacturing, assembly, and testing. We provide a full range of quality control and technical services.

## + Quality Control & Testing

We use an intelligent production system to monitor all production links in real-time, and do strict quality control testing, which greatly improves production efficiency and shortens the delivery time.

## Delivery Policy

If the product is in stock, it can usually be shipped within 24 hours, small orders are usually shipped within 5-7 days. We try our best to provide customers with an experience beyond expectations, and usually send orders before the forecast date to ensure customer satisfaction.

## Customer Service

We stands behind all our products and offer a 2-5 years warranty on our merchandise, which is provided directly by us. We test all our products in real environments and industry-standard testing facilities. Customer satisfaction has always been our top priority. Each of our customers will receive the greatest care and respect. Our customers make us.

## Best selection

Focus on providing the best solution at the best price. We strive to make UNIT SIGNAL your first choice in the market.

Unit Signal dedicates to achieve mutual development and concentrates on supplying reliable, beautifully-crafted, well-functioned and economical LED warning lights.

we are always looking for new partners to help our products reach the customers and we are committed to creating and delivering the latest and greatest products that fulfills the needs of our customers.

## **INNOVATION - EXCELLENCE - TRUST**

# UNIT SIGNAL INC