



INNOVATION-EXCELLENCE-TRUST



## UNIT SIGNAL INC

E-mail: [sales@unitsignal.com](mailto:sales@unitsignal.com)

Add : NO.988,Jinyuan Road,Dongwangli Industry Park,  
Yinzhou Area,Ningbo City,Zhejiang,China

[www.unitsignal.com](http://www.unitsignal.com)



UNIT SIGNAL INC

PRODUCT GUIDE

PUBLIC SAFETY  
WARNING LIGHTS AND  
SYSTEMS



# 13

## UNIT SIGNAL

PUBLIC SAFETY WARNING LIGHTS AND SYSTEMS

Ensure the safety of workers, first responders, and our community

### INNOVATION

Products engineered with purpose, built to last , and innovated with a forward vision

### EXCELLENCE

All products are built with materials of the highest quality in order to ensure performance with extreme durability and long lasting life

### TRUST

Products that you know you can trust and rely on



UNIT SIGNAL INC



Unit Signal was founded in 2014 of emergency vehicle lighting specializing in exterior and interior lights with a 5 year warranty on our merchandise. Every light we produce is constructed from only the best materials and has been thoughtfully designed to do its job in the most efficient and powerful way possible, allowing you to work harder, longer, and more productively. Today we continue to offer affordable, quality, and relentless innovation of emergency vehicle lighting that we proudly stand behind. We are glad to offer a complete line of vehicle warning lights and more. Whether it's a fleet, or POV, we can build you the perfect package.

# CONTENTS



## Grille & Surface Mounts

CT6.....	08
NT6.....	09
V-Series.....	11
TS-series.....	12
WS06.....	13
X9.....	14
UM24.....	15
Q3/Q4.....	16
H6.....	17
KL6.....	18
Z12.....	19
Y12.....	20
N6.....	22
M-Series.....	23
M12.....	24
EG6.....	25
G3.....	27
SL40.....	28

## LightBars & Minibars

NEO.....	30
Ronin.....	31
Marv.....	32
Phantom.....	33
Avata.....	34
SKL.....	35
NRO.....	36
Mavic.....	38
Matrix.....	40
Maxus.....	42
ET30/ET54/ET60.....	44
Matrix mini.....	45
M108.....	46
DY-series.....	48
DF12.....	49
VL10.....	50
VN48.....	51
DS48.....	53
MB-series.....	54
HT-series.....	56
DT-series.....	57
ALF60.....	58

## Traffic Advisors

## Dash & Deck & Visor

## Hideaway Light

H800.....	60
-----------	----

U1200.....	61
------------	----

U800.....	62
-----------	----

## Perimeter Lights

PC12/PC18.....	74
----------------	----

PC8.....	75
----------	----

PC16.....	76
-----------	----

PL8.....	77
----------	----

PL16.....	78
-----------	----

## Sirens & Speakers

MDS40.....	80
TM lighting mast.....	94
HM100.....	81
Flasher.....	95
S60.....	82
T2 tail lift light.....	96
CJB-100PN.....	83
RF06 road flares.....	97
CJB-100DT.....	84
Halo30 trailer tail light.....	98
CJB-100AD.....	85
JZ08 shoulder light.....	99
CJB-100CD.....	86
CJB-100RD/A.....	87
CJB-20001.....	88
S22/Z22.....	89
SK02.....	90
SK03.....	91
Other speakers.....	92

## Beacons

B20.....	64
----------	----

BS10.....	65
-----------	----

RC40/RC80.....	66
----------------	----

SR18.....	67
-----------	----

LF18.....	68
-----------	----

TB18.....	69
-----------	----

RD64.....	70
-----------	----

AR24.....	71
-----------	----

Spark.....	72
------------	----


# Grille & Surface Mounts



## Features:

- Brand new CT6 light, emergency lights for volunteer firefighters
- Powered by DC 10-30V
- Single color, dual color, or Trio color available
- 6 / 12 / 18 Pcs 3W LED with thin(12mm) design
- Aluminum base for efficient heat dissipation, UV-resistant PC
- With a gas-permeable membrane to disperse water vapor
- 50% power steady on functions available
- Built-in 20(single color)/25(dual color) selectable flash patterns with Pattern Memory
- Simultaneously or alternately between multiple units
- IP-67 Standard, Weatherproof
- Fully encapsulated for moisture, vibration, and corrosion resistance
- Long-life LEDs rated to 100,000 hours of reliable operation

## Dimension:



10-30V  
Voltage

20  
Flash Patterns

IP67  
Waterproof

CT6

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
10-30V	6PCS 3W 12PCS 3W 18Pcs 3W	18W	20-25	single dual Trio	Surface mount	ECE R65 XA1 XB1



10-30  
Voltage

12  
Flash Patterns

IP67  
Waterproof


Color:



Features:

- Brand new NT6 light
- Powered by DC 10-30V
- Single color or Dual color available
- Default with surface mount brackets and L-mount brackets
- 6 Pcs or 12Pcs 3W LED with width(15.8mm) design
- Aluminum base for efficient heat dissipation
- UV-resistant PC
- With gas-permeable membrane to disperse water vapor
- 50% power steady on functions available
- Built-in 12 selectable flash patterns with Pattern Memory
- Simultaneously or alternately between multiple units
- IP-67 Standard, Weatherproof
- Fully encapsulated for moisture
- Vibration and corrosion resistance
- Long life LEDs rated to 100,000 hours of reliable operation

Dimension:



NT6

Voltage	LED Power	Max Power	Flash Pattern	Colour
10-30V	6PCS 3W 12PCS 3W	18W	12	single dual

Mount	Certifications
surface mount, L-bracket	/




**12-24**  
Voltage

**18**  
Flash Patterns

**IP67**  
Waterproof

**Features:**

- V3/4/6 can be mounted on curved surfaces for different angles with 3M tape
- Compliant with ECE R65 and R10, SAE J595.
- Powered by DC 12-24V
- 3/4/6 Pcs CREE LEDs
- Single color or split color available
- New design program and easy to sync and alternate lights together
- Built-in 18 selectable flash patterns
- Pattern Memory available
- PC lens and PP material
- IP-67 Standard, Weatherproof
- Long-life LEDs rated to 100,000 hours of reliable operation

**Dimension:**

- V3: 114\*30\*9mm
- V4: 141\*30\*9mm
- V6: 196\*30\*9mm



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	3W CREE LEDs	9/12/18W	18	single or split	Surface mount 3M mount	ECE R65, R10 SAE Class1

11


**12-24**  
Voltage

**19**  
Flash Patterns

**IP67**  
Waterproof

**Features:**

- Compliant with ECE R65 and R10, SAE J595 class 1.
- Powered by DC 12-24V
- 3/4/6/12/18/24 Pcs CREE or Osram LEDs
- Single color or split color available
- Surface mount or 3M mount for optional choice
- New design program and easy to sync and alternate lights together
- Built-in 19 selectable flash patterns
- Pattern Memory available
- Aluminum base for efficient heat dissipation
- IP-67 Standard, Weatherproof
- Long-life LEDs rated to 100,000 hours of reliable operation

**Dimension:**

- TS03: 8.2\*3\*1cm
- TS04: 9.9\*3\*1cm
- TS06: 13\*3\*1cm
- TS12: 13\*4\*1cm
- TS18: 13\*5.5\*1cm
- TS24: 13\*6.5\*1cm

**TS**  
**-series**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	3W CREE LEDs / Osram LEDs	/	19	single or split	Surface mount 3M mount	ECE R65 R10 and SAE

12



**10-30**  
Voltage

**19**  
Flash Patterns


**IP67**  
Waterproof



#### Features:

- Powered by 10-30V
- 2 functions in 1 light
- Warning LED (6pcsx3W LEDs) with Scene LED (6pcsx4W LEDs)
- 19 Flash Patterns with Pattern Memory
- Wide-angle(105°) for scene light
- Meet ECE R65 Class 2 and SAE Class 1
- Synchronization function between multiple units
- Compactly sized for versatile application
- Heavy-duty aluminum housing(white or black)
- IP69K Standard
- Weatherproof and vibration-resistant design
- Reverse polarity protection
- A lifespan of up to 100,000 hours

#### Dimension:



**12-24**  
Voltage

**19**  
Flash Patterns

**IP67**  
Waterproof



#### Features:

- QUAD color available
- Powered by 12-24V
- 24pcs 3W High-intensity LEDs
- 19 Flash Patterns with Pattern Memory
- Surface mount or L-bracket mount
- 180° light spread model
- Synchronize or Alternate function
- IP-68 Standard
- Aluminum alloy base, UV-resistant PC,
- Multifunctional wire(3 modes wires)
- Perfect for mounting anywhere on your vehicle

**Dimension:** 136mm L \* 27mm W \* 15mm H



**WS06**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications	
10-30V	3W LEDs	18W	19	single or split	Surface mount	ECE R10,R65 Class2 SAE J595 Class2 R148,CAT13	13

**X9**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications	
12-24V	24Pcs 3W	27W	19	Single Dual Quad	Surface mount L-brackets	/	14



**12-24**  
Voltage

**29**  
Flash Patterns


**IP67**  
Waterproof

Color:  


Features:

- Powered by DC 12-24V
- 24 Pcs 3W LEDs
- Single color or Dual color available
- Dim function available(50% power)
- Surface mount or under mirror mount brackets for optional choice
- New design program and easy to sync lights together
- Built-in 29 selectable flash patterns
- Pattern Memory available
- Aluminum base for efficient heat dissipation
- IP-67 Standard, Weatherproof
- Long-life LEDs rated to 100,000 hours of reliable operation

Dimension:



**12-24**  
Voltage

**19**  
Flash Patterns

**IP67**  
Waterproof

Color:  


Features:

- 3/4 Pcs 3W CREE or Osram LEDs and 4/6 Pcs 0.5W white LEDs for DRL
- Compliant with ECE R65 and R10, SAE J595 class 1.
- Powered by DC 12-24V
- Single color available
- Surface mount or 3M mount for optional choice
- New design program and easy to sync and alternate lights together
- Built-in 19 selectable flash patterns
- Pattern Memory available
- IP-67 Standard, Weatherproof
- Long-life LEDs rated to 100,000 hours of reliable operation

Dimension: Q4: 57 x 45 x 11mm  
Q3: 86.5 x 35.5 x 9.8mm



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	24Pcs 3W	36W	29	single or dual	Surface mount or under mirror mount brackets	/

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	3/4pcs 3W 4/6pcs 0.5W	9/12W	19	single color	Surface mount 3M mount	ECE R65, R10 and SAE



**10-30**  
Voltage

**19or12**  
Flash Patterns

**IP67**  
Waterproof

Color:  


#### Features:

- Powered by DC 10 -30V
- Single or Dual color is available now
- 6/12pcs high-intensity LED with optic lenses
- Hood mount or L-bracket mount
- Built-in 19 or 12 selectable flash patterns with Pattern Memory
- Super low profile discreet mounting
- Simultaneously or alternately between multiple units
- Aluminum base for efficient heat dissipation
- IP-67 Standard, Weatherproof, and vibration resistant design
- Long-life LEDs rated to 100,000 hours of reliable operation
- Reverse polarity protection

#### Dimension:



**10-30**  
Voltage

**19**  
Flash Patterns


**IP67**  
Waterproof

Color:  


#### Features:

- Powered by DC 10-30V
- 6/12pcs high intensity LED with optic lenses
- Extra steady on functions for vehicle identification or illumination.
- Built-in 19 selectable flash patterns with Pattern Memory
- Super low profile discreet mounting
- Simultaneously or alternately between multiple units
- Aluminum base for efficient heat dissipation
- IP-67 Standard, Weatherproof and vibration resistant design
- Long life LEDs rated to 100,000 hours of reliable operation
- Reverse polarity protection

#### Dimension:



Voltage	LED Power	Max Power	Flash Pattern	Colour
10-30V	6/12Pcs 3W	18W	19 or 12	Single Split Dual

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
10-30V	6/12pcs 3W	18W	19	single or dual	Hood mount	/


**12-24**  
Voltage

**16/10**  
Flash Patterns

**IP67**  
Waterproof


Color:



Features:

- Powered by 12-24V
- 18Pcs 3W high intensity LED
- 16/10 Flash Patterns with Pattern Memory
- Synchronization between multiple units
- Low-profile thickness, Compactly sized for versatile application
- Heavy-duty aluminium housing
- IP-67 Standard
- Weatherproof and vibration resistant design
- Black flange included for protection and stealth
- Lifespan of up to 100,000 hours
- Meets or Exceeds ECE R65 Standards

Dimension:

**Z12**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	12PCS 3W	36W	16/10	single or dual	Surface mount	/

19


**12-24**  
Voltage

**16/10**  
Flash Patterns

**IP67**  
Waterproof

Color:



Features:

- Powered by 12-24V
- Dual-color available
- 3W high-intensity LED
- 16/10 Flash Patterns with Pattern Memory
- Synchronization or alternate between multiple units
- Low-profile thickness, Compactly sized for versatile application
- Heavy-duty aluminum housing
- IP-67 Standard
- Weatherproof and vibration-resistant design
- Black flange included for protection and stealth
- A lifespan of up to 100,000 hours

Dimension:

**Y12**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	3W LEDs	36W	16/10	single or dual	Surface mount	/

20



[Surface Mounts](#) [LightBars](#) [Dash & Deck & Visor](#) [Traffic Advisors](#) [Hideaway](#) [Beacons](#) [Perimeter Lights](#) [Sirens & Speakers](#)

Color:



Features:

- Powered by 12-24V
- High intensity LED
- 19 Flash Patterns with Pattern Memory
- 180° light spread model
- Single color, Dual color, Trio color available
- Synchronize or Alternate function
- IP-68 Standard; a gas-permeable membrane to disperse water vapor - suitable for high-altitude use
- Weatherproof and ready for exterior mounting.
- Aluminum alloy base, UV-resistant PC, Multifunctional wire
- Perfect for mounting anywhere on your vehicle
- Lifespan of up to 100,000 hours





12-24  
Voltage

19  
Flash Patterns

IP68  
Waterproof

**N6**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	6PCS 3W	18W	19	single dual trio	Surface mount	/





**12-24**  
Voltage

**16**  
Flash Patterns


**IP67**  
Waterproof

Color:

Features:

- Powered by 12-24V
- 4 high intensity LED with optic lenses
- 16 Flash Patterns with Pattern Memory (single color / split color)
- Synchronization between multiple units
- Compactly sized for versatile application
- Built in heat sink
- Black flange included for protection and stealth
- Virtually Out of Sight
- Extremely Bright-Highly Visible when ON!
- IP-67 Standard
- Weatherproof ready for exterior mounting. (Not submersible)
- Lifespan of up to 100,000 hours
- Meets or Exceeds SAE J595 Standards

Dimension:



**12-24**  
Voltage

**16**  
Flash Patterns

**IP67**  
Waterproof


  
UNIT SIGNAL INC

Color:

Features:

- Powered by 12-24V
- 12 high intensity LED with optic lenses
- 16 Flash Patterns with Pattern Memory
- Synchronization between multiple units
- Compactly sized for versatile application
- Built-in heat sink
- Black flange included for protection and stealth
- IP-67 Standard
- Weatherproof ready for exterior mounting. (Not submersible)
- The lifespan of up to 100,000 hours

Dimension: 121mm L X 47.4mm W X 14.5mm H



	Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
M3	12-24V	3PCS 3W	9W	16	single or split	Surface mount	/
M4		4PCS 3W	12W				
M6		6PCS 3W	18W				

	Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
	12-24V	12PCS 3W	36W	16	single or split	Surface mount	/



10-33  
Voltage

12  
Flash Patterns

IP67  
Waterproof

EG6

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications	25
10-33V	3W LEDs	18W	12	single dual trio	Surface mount 3M mount L-bracket mount hood mount	ECE R65 XA2&XB2 and SAE	


Color:



Features:

- Powered by DC 10-33V
- 6 Pcs or 12Pcs 3W LEDs with new super thin(7mm) design
- Single color or Dual color available
- Surface mount or 3M mount or L-bracket mount or hood mount for optional choice
- Plastic of Optics lens from Degussa(GER)
- and LED Driver from MPS(UK)
- Extra steady on functions for vehicle identification or illumination.
- Built-in 12 selectable flash patterns with Pattern Memory
- Simultaneously or alternately between multiple units
- Aluminum base for efficient heat dissipation
- IP-67 Standard, Weatherproof
- Long life LEDs rated to 100,000 hours of reliable operation
- Reverse polarity protection

Dimension:




**12-24**  
Voltage

**14**  
Flash Patterns

**IP67**  
Waterproof

**G3**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	3Pcs 3W	9W	14	single	Surface mount	/

27

**SL40**

Color:    
**Features:**

- Powered by DC 12V
- Single color available
- 3 Pcs 3W LED
- G3 can be installed as a tail light(10% intensity) and brake light(70% intensity)
- Tiny size with only 1-inch width and height
- Aluminum base for efficient heat dissipation
- UV-resistant PC
- Built-in 14 selectable flash patterns with Pattern Memory
- Simultaneously or alternately between multiple units
- IP-67 Standard, Weatherproof
- Long-life LEDs rated to 100,000 hours of reliable operation

**Dimension:**

- 8.64cm L \* 2.54cm W \* 2.67cm H


**9-32**  
Voltage      **Steady on**  
Flash Patterns      **IP67**  
Waterproof

Color: 
**Features:**

- Powered by DC 9-32V
- Flood beam
- Die-cast aluminum housing
- Scene LED (40pcsx1W Osram LEDs), 4000LM
- Surface mounting - 45-degree tilt
- Color temperature 6000K
- Synchronization function between multiple units
- Compact size for versatile application
- Black or white chrome housing
- IP-67 Standard
- Weatherproof and vibration-resistant design

**Dimension:** 251mm L \* 38mm W \* 54mm H

CISPR25 CLASS 3  
FCC Part 15B  
ECE R10

28

# LightBars & Minibars



Features:

- Slim design(25mm), 360° High-Intensity Versatile
- Dual color is also available
- Powered by 10-30V
- High intensity 3W LEDs
- ST controller or hard wired
- 16 available flash patterns with Pattern Memory
- LED take-down and alley lights, arrow lights: right, left, center-out
- Lifespan of LED up to 100,000 hours
- IP67 Waterproof Exterior Light bar
- Includes 4m of cable with controller(on/off and mode) provided
- Magnet mount or Gutter Mount



10-30V  
Voltage

16  
Flash Patterns

IP67  
Waterproof



NEO

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
10-30V	3W LEDs	/	16	single split dual	Magnet mount Gutter Mount	Pending



**12-24V**  
Voltage

**19**  
Flash Patterns

**IP67**  
Waterproof

**Ronin**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	3W LEDs	/	19	single split dual	Magnet mount Gutter Mount	/



Features:

- Powered by 12V or 12-24V
- Single or split-color or Dual color available
- 132pcs 3W Super bright LEDs
- 19 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- The default handheld controller provided
- The front and rear can be controlled separately
- Arrow lights, takedown, alley lights, cruise mode, 50% power, etc
- A lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Lightbar
- Magnet mount or Gutter Mount

Dimension:

- 120cm L \* 28cm W \* 9cm H



**12-24V**  
Voltage

**31**  
Flash Patterns

**IP67**  
Waterproof

**Marv**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12V or 12-24V	3W LEDs	/	31	single split	Magnet mount Gutter Mount	/



Features:

- Powered by 12V or 12-24V
- Single or split-color combo available
- 3W Super bright LEDs
- 31 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- Default handheld controller provided
- Takedown, alley lights, All steady, cruise, Aux function available
- Rear Arrow stick directions: right, left, center-out
- The lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Lightbar
- Black aluminum top housing
- Magnet mount or Gutter Mount

Dimension:

- 18"/27"/36"/48"/55" L \* 11.4" W \* 3.4" H (with feet)





**12-24V**  
Voltage

**14**  
Flash Patterns

**IP67**  
Waterproof

Color:




Features:

- The extremely slim design of 0.96 inches(2.5cm)
- Powered by 12-24V
- Compliant with ECE R65 TA2, ECE R10, SAE J845 CLASS 2, CISPR 25 CLASS 3
- Single amber color available
- 3W Super bright LEDs
- 14 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- Default with cigar plug
- Optional two other controllers for choice
- Takedown, alley lights, cruise, arrow light function available
- The lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Lightbar
- Black aluminum top housing
- Magnet mount or Gutter Mount

Dimension:

- 24"/30"/42"/48"/60"/72" L \* 8.6" W \* 0.96" H



## Phantom

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	3W LEDs	/	14	Amber	Magnet mount Gutter Mount	ECE R65 TA2, ECE R10, SAE J845 CLASS 2, CISPR 25 CLASS 3



**12-24**  
Voltage

**14**  
Flash Patterns

**IP67**  
Waterproof

Color:




Features:

- The extremely slim design of 2.35cm
- Powered by 12-24V
- Compliant with ECE R65 TA2, ECE R10, SAE J845 CLASS 2, CISPR 25 CLASS 3
- Single amber color available
- 3W Super bright LEDs
- 14 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- Default with cigar plug
- Optional remote controllers for choice
- The lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Lightbar
- Black aluminum top housing
- Gutter Mount

Dimension:

- 590/1040/1200/1500mm L \* 204mm W \* 23.5mm H



## Avata

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
DC12-24V	3W LEDs	/	14	Amber color	Gutter Mount	ECE R65 TA2, ECE R10, SAE J845 CLASS 2, CISPR 25 CLASS 3


**12V**  
Voltage

**25**  
Flash Patterns

**IP67**  
Waterproof

## Color:



## Features:

- The extremely slim design of 1 inch (2.54cm)
- Powered by 12V
- Single or split-color combo available
- Generation III 3W Super bright LEDs
- 25 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- Default with cigar plug
- Optional other controllers for choice or hard wired
- Takedown, alley lights, arrow light function available
- The lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Lightbar
- Double-layer aluminum alloy top housing, Weather-proof housing
- Magnet mount or Gutter Mount

## Dimension:

- 24"30"/42"/47"/59"/72" L \* 11" W \* 4" H (include feet)



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
DC12V	3W LEDs	/	25	single split dual	Gutter Mount	/


**12/12-24V**  
Voltage

**31**  
Flash Patterns

**IP67**  
Waterproof

## Color:



## Features:

- Powered by DC 12V or 12-24V
- Single or split-color combo or dual color available
- 3W Super bright LEDs
- 31 available flash patterns with Pattern Memory
- Default with cigar plug or hard wired
- Optional other controllers for choice
- Takedown, alley lights, and arrow light functions available
- A lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Lightbar
- Double-layer aluminum alloy top housing
- Weather-proof
- Magnet mount or Gutter Mount

## Dimension:

- 13/23/33/43/53 inch(L) X 4.85"(W) X 0.98"(H) without feet



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
DC12V DC12-24V	3W LEDs	/	31	single split dual	Gutter Mount Magnet Mount	/



## Mavic Lightbar

The Mavic LED Full Size Light Bar features 1-watt or 3-watt high intensity Super bright LEDs with built-in ultra bright take downs and alleys. Universal gutter brackets and controller included for easy installation & use.



## Mavic

10-30  
Voltage

16  
Flash Patterns

IP67  
Waterproof



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
10-30V	3W LEDs	/	16	single split dual	Magnet mount Gutter Mount	ECE R65 TB1 ECE R65 TA1 ECE R10

Surface Mounts **LightBars** Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers


Color:



Features:

- Dual-color is available now!!!
- Powered by 10-30V
- High intensity 3W Super bright LEDs
- 16 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- LED take-down and alleys
- Arrow stick directions: right, left, center out
- Lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Light bar
- Optional Control Box available for purchase
- Includes 4m of cable with controller(on/off and mode) provided
- Magnet mount or Gutter Mount
- Meets or Exceeds ECE R65 TB1, ECE R65 TA1, ECE R10

Dimension:





# Matrix Lightbar

The Matrix lightbar is the first Trio-color LED warning lightbar on the market today, and offers universal gutter brackets and controller.




Color:



Features:

- First Trio-color LED warning lightbar on the market
- Powered by 10-30V
- High intensity 1W or 3W Super bright LED
- Energy saving, low consumption, environmental protection
- 15 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- LED take-down and alley lights
- Arrow stick directions: right, left, center out
- Lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Light bar
- Includes 4m of cable with controller(on/off and mode) provided
- Gutter Mount available
- Meets or Exceeds ECE R65 TA1, ECE R65 TB1, ECE R10

Dimension:



10-30  
Voltage

15  
Flash Patterns

IP67  
Waterproof

Matrix

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
10-30V	3W LEDs	/	15	single dual trio	Magnet mount Gutter Mount	ECE R65 TA1 ECE R65 TB1 ECE R10

# Maxus Lightbar

Red/Blue/Black/Clear/Amber lens available for the Maxus lightbar. Choose from Single or Dual or Trio-color version.



Surface Mounts **LightBars** Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers

Color:



Features:

- Single or Dual or Trio-color LED warning lightbar
- Powered by 12-24V
- High intensity 3W Super bright LED
- Red/Blue/Black/Clear/Amber lens available
- Energy saving,environmental protection
- 15 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- Take-down, alley lights, arrow lights available
- Lifespan of up to 100,000 hours
- IP67 Waterproof Exterior Light bar
- Includes 4m of cable with controller(on/off and mode) provided
- Default Gutter Mount available




12-24  
Voltage

15  
Flash Patterns

IP67  
Waterproof

Maxus

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	3W LEDs	/	15	single dual trio	Magnet mount Gutter Mount	/





## ET30 Minibar

The 12inch ET30 LED Mini Light Bar is a compact lightbar designed with 30pcs 3-watt LEDs and 12 available flash patterns.



Surface Mounts **LightBars** Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers



12-30  
Voltage

12/14  
Flash Patterns

IP67  
Waterproof

**ET30  
ET54  
ET60**

	Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
ET30	12-30V	30PCS 3W	90W	12	single and split	Magnet mount	/
ET54		54PCS 1W	54W	14		Screw mount	
ET60		60PCS 3W	180W	12			




### Features:

- Powered by 12-30V
- Mini LED strobe light
- 1W or 3W LEDs
- 14 Flash Patterns with Pattern Memory
- Lifespan of up to 50,000 hours
- 360°High-Intensity Illumination
- Includes 3m of cable from light bar to cigarette plug
- Weather-proof housing
- Includes Magnetic-Mounting or screw, Easy Installation
- Robust and Solid

### Dimension:

- ET30: 30.5\*18.5\*4.5cm
- ET54: 28\*16.5\*4.5cm
- ET60: 44\*22\*4.5cm




**10-30**  
Voltage

**15**  
Flash Patterns

**IP67**  
Waterproof


## Color:



## Features:

- Single or Dual color available
- Powered by 10-30V
- High intensity 1W or 3W Super bright LED
- Magent mount
- Feet covered with rubber protector
- 15 available flash patterns with Pattern Memory
- 360° High-Intensity Versatile, Multi-Purpose Light Bar
- IP67 Waterproof Exterior Light bar
- Includes 4m of cable with controller provided
- Optional controller for purchase
- Meets or Exceeds ECE R65 TA1, ECE R65 TB1, ECE R10

## Dimension:


**12-24**  
Voltage

**15**  
Flash Patterns

**IP67**  
Waterproof

## Color:



## Features:

- Powered by 12-24V
- Mini amber LED bar
- 108Pcs 0.3 Watt LEDs
- 15 Flash Patterns with Pattern Memory
- Lifespan of up to 100,000 hours
- 360°High-Intensity Illumination
- Includes 3m of cable from the light bar to the cigarette plug
- Weather-proof housing
- Magnetic-Mounting

## Dimension:

- 420 x 207 x 149mm



# Dash & Deck & Visor



## DY-series

	Voltage	LED Power	Max Power	Flash Pattern	Colour
DY4	12V	3W	12W	16	single
DY6		3W	18W		dual
DY16		16PCS 3W	48W		
DY24		24PCS 3W	72W		

Mount	Certifications
Suction cup	/



#### Features:

- Powered by DC 12V
- Single color or Dual color available
- Light with suction cups
- 3-watt high-intensity LED
- 16 Flash Patterns with Pattern Memory
- 6 suction cups for stabilized mounting
- A lifespan of up to 100,000 hours
- Cigarette plug with On/Off switch and flash pattern changer

#### Dimension:

- DY4: 118-91-36mm
- DY6: 118-91-36mm
- DY16: 454-91-36mm
- DY24: 454-91-36mm





12  
Voltage      16  
Flash Patterns      /  
Waterproof

DF12

Voltage	LED Power	Max Power	Flash Pattern	Colour
12V	12PCS 3W	36W	16	single dual



#### Features:

- Powered by DC 12V
- Single color or Dual color available
- Light with suction cups
- 12PCS 3-watt high-intensity LED
- 16 Flash Patterns with Pattern Memory
- 3 suction cups for stabilized mounting
- A lifespan of up to 100,000 hours
- Cigarette plug with On/Off switch and flash pattern changer

#### Dimension:

- 26.3(L) X 8.8(W) X 2.8(H)cm



12V  
Voltage      16  
Flash Patterns      /  
Waterproof

VL10

Voltage	LED Power	Max Power	Flash Pattern	Colour
DC 12V	3W LEDs	/	16	single split



#### Features:

- Powered by 12V
- Single or Split color available
- Bright 3-Watt LEDs
- 16 flash patterns with arrow mode
- Default buttons at the rear of the light (on/off, pattern change, takedown, arrow)
- Middle two modules for the white takedown function
- Flash pattern memory
- Sleek, durable housing
- Includes universal brackets

#### Dimension:

- Half: 435mm Lx 160mm( Left Width) x 35mm H





12V  
Voltage

41  
Flash Patterns

/  
Waterproof



Features:

- Powered by 12V
- Single or Split or Dual color available
- 48/96Pcs 3-Watt LEDs
- (48) 3-Watt LEDs - (48) 3-Watt Takedown LEDs
- 41 flash patterns
- Default cigar plug with on/off & flash pattern & takedown
- Flash pattern memory
- Sleek, durable housing
- Includes universal brackets

Dimension:

- VN48 visor light bar
- Default cigar plug
- Universal visor mount brackets
- 3m of cable with cigarette plug provided
- Half: 450mm L x 105mm W x 30mm H



**VN48**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12V	48PCS 3W 96PCS 3W	144W	11 41	single or split dual	Brackets mount	/

51





12-24V      12      /  
Voltage      Flash Patterns      Waterproof

**DS48**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
DC 12-24V	48Pcs 0.5W	24W	12	single or split	Velcro Tape	/

53



#### Features:

- Velcro Tape Mount light
- It can be easily mounted to vehicle's Front windshield.
- Powered by DC 12 -24V
- 48 Pcs 0.5W LEDs
- Single color or split color available(red/blue/amber/white/green combo)
- Built-in 12 selectable flash patterns
- Pattern Memory available
- 2.3m of cable with cigarette plug(on/off) provided
- Long life LEDs rated to 50,000 hours of reliable operation

#### Dimension:

- 29.8cm L x 9cm W x 1.5 cm H



12      steady on      /  
Voltage      Flash Patterns      Waterproof

**MB-series**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12V	/	/	steady on	amber/red/blue	Suction cup	/



#### Features:

- Powered by DC 12V
- Amber/red/blue color available
- High-intensity LED
- Steady on function
- 3 suction cups for stabilized mounting
- A lifespan of up to 100,000 hours
- Cigarette plug with On/Off switch

#### Dimension:

- 25,4 cm L x 4,6 cm W x 3,8 cm L



54

# Traffic Advisors



HT-series



Surface Mounts LightBars Dash & Deck & Visor **Traffic Advisors** Hideaway Beacons Perimeter Lights Sirens & Speakers



12/24  
Voltage

16  
Flash Patterns

IP67  
Waterproof

Features:

- Powered by 12VDC or 24VDC
- TIR or Linear lens available.
- Single color or Dual-color or Trio color available
- 6pcs 3 Watt high power LEDs in each module
- 16 Flash Patterns with Pattern Memory
- 3 Selectable directional flash patterns
- Powerful, Compact Light Bar/ Sleek, durable casing
- Waterproof for Exterior Mounting, IP67
- A lifespan of up to 100,000 hours
- Includes Brackets and 10ft cable
- Optional cigarette plug with on/off & flash pattern controls or hard wired
- Optional 4 switches Controller available for purchase

Dimension:

- 23/45/68/90cm L X 4.8cm W X 3.6cm H



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
DC 12V or 24V	3W LEDs	/	16+3 Arrow patterns	single dual trio	Brackets mount	/



12 or 24  
Voltage

16  
Flash Patterns

IP67  
Waterproof

Color:



Features:

- Powered by 12VDC or 24VDC
- Running board led emergency lights
- Single color or Dual-color or Trio color available
- Green color and purple strobe lights
- 6pcs 3 Watt high power LEDs in each module
- 16 Flash Patterns with Pattern Memory
- 3 Selectable directional flash patterns
- Powerful, Compact Light Bar/ Sleek, durable casing
- Waterproof for Exterior Mounting, IP67
- The lifespan of up to 100,000 hours
- Includes Brackets and 10ft cable
- Optional cigarette plug with on/off & flash pattern controls or hard wired
- Optional 4 switches Controller available for purchase

Dimension:

- 26/52/78/104cm L X 8.8cm W X 2.8cm H



12-24  
Voltage

3  
Flash Patterns

IP67  
Waterproof

Color:



Features:

- Most cost-effective arrow lights
- Input voltage 12-24VDC
- 344pcs high power LEDs
- 3 available directional flash patterns(right, left, and center out)
- Default with 3-switch controller
- Bracket mount
- Lifespan of up to 100,000 hours

Dimension:



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12V or 24V	3W LEDs	/	16+3 Arrow patterns	Single Dual Trio	Brackets mount	/

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	344PCS 0.5W	/	3	Amber	bracket mount	/

# Hideaway Light



Color:



Features:

- Powered by 10-30V
- Each unit consists of 8 Pcs 3-watt high-intensity LEDs
- Two types of lenses are available (high design lens, low design lens)
- Dual color is available (amber-blue, amber-white, blue-white, red-blue, and red-white)
- 32 Flash Patterns with Pattern Memory
- Multiple modules can be wired together for synchronized flash
- Install the LED module into a 1" cut-out in the existing headlight or taillight lamp assembly, or use the mounting flange to mount it to the vehicle surface wherever desired
- Good for surface or internal mount within headlight, tail light, and various setups on personal emergency vehicles
- Lifespan of up to 100,000 hours
- 100% Waterproof
- Easily replaces traditional hideaway strobe with existing 1" hole



10-30  
Voltage

32  
Flash Patterns

IP67  
Waterproof

**H800**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
10-30V	8PCS 3W	24W	32	single or dual	Surface mount	/




**10-30**  
Voltage


**19**  
Flash Patterns

**IP67**  
Waterproof


Features:

- Powered by 10-30V
- Each unit consists of 12Pcs 3-watt high intensity LEDs
- 19 Flash Patterns with Pattern Memory
- Good for surface or internal mount within head light, tail light, and various setups on personal emergency vehicles
- Lifespan of up to 100,000 hours
- 100% Waterproof
- Easily replaces traditional hideaway strobe with existing 1" hole

Dimension:



## U1200

	Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
U1200	10-30V	12PCS 3W	36W	19	single or dual	Surface mount	/
U1200 eco		8PCS 3W	24W				

## U800

	Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
	12-24V	8PCS 3W	24W	16	single or split	Surface mount	/


**12-24**  
Voltage

**16**  
Flash Patterns

**IP67**  
Waterproof


Features:

- Powered by 12-24V
- Each unit consists of 8 high intensity LEDs
- 16 Flash Patterns with Pattern Memory
- Tiny Stealth Light for Head and Tail Lights
- Versatile application with surface mounting design and internal mounting within light assemblies
- Lifespan of up to 100,000 hours
- 100% Waterproof (not submersible)
- Easily replaces traditional hideaway strobe with existing 1" hole
- Meets or Exceeds SAE J595 Standards

Dimension:



# Beacon



**B20**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	20pcs 3W	20W	8	single color	Permanent mount Magnet mount Flexi Din mount	ECE R65 TA1 TB1 ECE R10

**12-24**  
Voltage

**8**  
Flash Patterns

**IP67**  
Waterproof



Surface Mounts LightBars Dash & Deck & Visor Traffic Advisors Hideaway Beacons Perimeter Lights Sirens & Speakers

Color:



Features:

- Powered by 12-24V
- 20Pcs 3W LEDs
- Single-color LEDs available (Amber, Blue)
- Amber, Blue lenses are available
- 8 flash patterns provide
- IP67 waterproof design
- Permanent mount, Magnet mount, or Flexi Din mount available
- Lifespan of up to 100,000 hours
- UV-stabilized lens resists fading
- Meet and exceed ECE R65 TA1; TB1; ECE R10

Dimension:

- $\phi 130.5\text{mm} \times 107\text{mmH}$




**BS10**

Voltage	LED Power	Max Power	Flash Pattern	Colour
12-24V	10pcs 3W	15W	9	Amber

Mount	Certifications
Permanent mount	ECE R65 TA1 ECE R10

65

Color:




## Features:

- Built-in back up alarm with >100 dB speaker
- 10pcs LEDs
- With Buzzer(104 dB), one wire to control the buzzer
- Low profile design
- Amber colors LEDs available
- 9 flash patterns provide
- IP67 waterproof designed
- Permanent mount available
- A lifespan of up to 100,000 hours
- UV-stabilized lens resists fading
- Meet and exceed ECE R65 TA1; ECE R10

## Dimension:

- Top Ø 110mm\* Bottom 130mm\*85mmH


**RC40  
RC80**

Voltage	LED Power	Max Power	Flash Pattern	Colour
DC 5V USB charger	40 or 80pcs 0.5W	20W/40W	2	Amber


Color:



## Features:

- Rechargeable Beacon with DC5V, USB charger
- 40 or 80pcs 0.5W LEDs
- With Buzzer(104 dB), a switch inside the beacon
- Low profile design
- Amber colors LEDs available
- 2 flash patterns provide(single flash and double flashes)
- IP67 waterproof designed
- Magnet mount available
- A lifespan of up to 100,000 hours
- UV-stabilized lens resists fading
- Meet and exceed ECE R65 TA1; ECE R10

## Dimension:



66

**12-24**
**Voltage**
**7**
**Flash Patterns**
**IP67**
**Waterproof**

**Color:**

**Features:**

- Powered by 12-24V
- 18Pcs 1W LEDs
- Multi-units can be synced together (20pcs)
- Low profile design
- Single colors LEDs available (Amber, Blue, Red, White, Green)
- Amber, Blue, Clear, and Green lens available
- 7 flash patterns provide
- IP67 waterproof designed
- Permanent mount, Magnet mount, or Flexi Din mount available
- Lifespan of up to 100,000 hours
- UV-stabilized lens resists fading
- Meet and exceed ECE R65 TA1; TB1; ECE R10; UKCA; CISPR 25 Class 3.

**Dimension:**

- $\phi 112\text{mm} \times 46\text{mmH}$


**10-30**
**Voltage**
**22**
**Flash Patterns**
**IP67**
**Waterproof**

**Color:**

**Features:**

- Powered by 10-30V
- 18Pcs high intensity GenII LEDs
- distributed on the nine surfaces
- IP67 waterproof designed
- 22 Available Flash Patterns(include rotation flash mode)
- Luminous flux > 540lm
- Optional Magnetic and Permanent mount
- Amber/Red/Blue/Clear lens available
- Lifespan of up to 100,000 hours
- UV stabilized lens resists fading

**Dimension:**

- $\phi 153\text{mm} \times 83\text{mmH}$


**SR18**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12-24V	18PCS 1W	18W	7	single	Permanent mount / Magnet mount / Flexi Din mount	ECE R65 ECE R10 UKCA CISPR 25 Class 3

**67**
**LF18**

Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
10-30V	18PCS 1W	18W	22	R B A W	Permanent mount / Magnet mount / Extendable pole mount	

**68**



12  
Voltage

84  
Flash Patterns

IP67  
Waterproof

Color:



Features:

- First trio color beacon in the market
- Powered by 12V
- 18Pcs high intensity LEDs
- Single or Dual or Trio color available
- 7 modes provide (color1, color2, color3, color1&2, color1&3, color2&3, color1&2&3)
- IP67 waterproof designed
- 84 Available Flash Patterns
- Permanent mount, Magnet mount, Clear lens available
- Lifespan of up to 100,000 hours
- UV stabilized lens resists fading

Dimension:

- $\Phi 145\text{mm} \times \Phi 110\text{mm} \times 125\text{mmH}$



12-24V  
Voltage

11  
Flash Patterns

IP67  
Waterproof

Color:



Features:

- Powered by 12-24V
- 64Pcs 0.5W LEDs
- Single or split color available
- Clear lens or amber lens available
- 11 flash patterns
- IP67 waterproof designed
- Magnet mount
- Lifespan of up to 100,000 hours
- UV-stabilized lens resists fading

Dimension:

- $\Phi 185\text{mm} \times \Phi 75\text{mm H}$





**12-24**  
Voltage

**12**  
Flash Patterns

**IP67**  
Waterproof


Color:



**Features:**

- Economical beacon
- Powered by 12-24V
- Each unit consists of 24 high intensity LEDs.
- IP67 rated weather-proof housing (not submersible).
- 12 Available Flash Patterns
- Max output of 2 Amps
- Optional magnetic mount with cigarette
- plug model or Permanent mount
- Lifespan of up to 100,000 hours
- UV stabilized lens resists fading

**Dimension:**



**10-30**  
Voltage

**8**  
Flash Patterns

**IP67**  
Waterproof

Color:



**Features:**

- Energy-saving beacon light
- Powered by 10-30V
- 12Pcs high intensity LEDs.
- Amber and Red lens available
- IP67 Double waterproof designed
- 8 Available Flash Patterns (including rotating)
- Max output of 0.52 Amps
- Optional Magnetic and Permanent mount
- 2.8m of cable with cigarette plug provided
- Lifespan of up to 100,000 hours
- UV stabilized lens resists fading,
- strong tooth structure and stylish design

**Dimension:**



# Perimeter Lights



Color:



Features:

- 7x3 and 6x4 perimeter lights
- Single or Dual colors available
- Brake, tail, turn, dim function available
- Voltage 12-24 VDC
- 12/24, 18/36 High-power 5-watt LEDs
- Provides 180° light spread
- Available with up to 37 flash patterns
- Amber, Red, Blue, or Clear Lenses are available
- Easy to Install or Retrofit
- Weather and vibration-resistant
- Covered with rubber protector
- Synchronization and alternating between Multiple modules
- Includes chrome bezel



12-24

Voltage

37

Flash Patterns

IP67

Waterproof

**PC12  
PC18**

Voltage

12-24V

LED Power

12/18PCS 5W

Max Power

60W/90W

Flash Pattern

37

Colour

single  
split  
dual

Mount

Surface mount

Certifications

/




**12/24**  
Voltage

**18**  
Flash Patterns

**IP67**  
Waterproof

Color:  
    
**Features:**

- LED technology provides better lighting with far less amperage than halogen
- Voltage 12-24 VDC
- 8 High power 3-watt LEDs
- Provides 180° light spread
- Available with up to 18 flash patterns
- Single Colors or Split Color available
- Amber, Red, Blue, or Clear Lenses are available
- Easy to Install or Retrofit
- Weather and vibration resistant
- Covered with rubber protector
- Synchronization between Multiple modules
- Includes chrome bezel

**Dimension:**


Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12V or 24V	8PCS 3W	24W	18	single or split	Surface mount	/



**12/24**  
Voltage

**18**  
Flash Patterns

**IP67**  
Waterproof

Color:  
    
**Features:**

- LED technology provides better lighting
- with far less amperage than halogen
- Voltage 12 or 24 VDC
- 16 High power 3-watt LEDs
- Available with up to 18 flash patterns
- Single Colors or Split Color available
- Amber, Red, Blue or Clear Lenses available
- Easy to Install or Retrofit
- Covered with rubber protector
- Weather and vibration resistant
- Synchronization between Multiple modules
- Includes chrome bezel

**Dimension:**


Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12V or 24V	16PCS 3W	48W	18	single or split	Surface mount	/



12/24  
Voltage

18  
Flash Patterns

IP67  
Waterproof


Color:



Features:

- 6x4 Perimeter Mount Lights
- Voltage 12 or 24 VDC
- 8 Pcs High power 3-watt LEDs
- Provides 180°light spread
- Chrome bezel available
- Available with up to 18 flash patterns
- Single Colors or Split Color available
- The clear/amber/red/blue lens is available
- Easy to Install or Retrofit
- Covered with rubber protector
- Weather and vibration resistant
- Synchronization between Multiple modules

Dimension:



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12V or 24V	8PCS 3W	24W	18	single or split	Surface mount	/



12/24  
Voltage

18  
Flash Patterns

IP67  
Waterproof


Color:



Features:

- LED technology provides better lighting
- with far less amperage than halogen
- Voltage 12 or 24 VDC
- 16 High power 3-watt LEDs
- Provides 180°light spread
- Available with up to 18 flash patterns
- Single Colors or Split Color available
- Amber, Red, Blue or Clear Lenses available
- Easy to Install or Retrofit
- Covered with rubber protector
- Weather and vibration resistant
- Synchronization between Multiple modules

Dimension:



Voltage	LED Power	Max Power	Flash Pattern	Colour	Mount	Certifications
12V or 24V	16PCS 3W	48W	18	single or split	Surface mount	/

# Sirens & Speakers



## Features:

- MDS40 Police motorcycle siren and speaker with strobe light head
- 1. 2pcs 40W speakers(6 ohm), DC12V
- 2. UV-resistant PC lens
- 3. 10pcs 1W LEDs
- 4. Set in one package: 6



12V  
Voltage

120-130  
Sound

6Ω  
Impedance

**MDS40**

Voltage	Sound	Max Power	Output	Impedance	Accessories	Tone
12V	120-130dB	40W x 2=80W	/	6Ω	/	3



9V to 15V / /  
Voltage Sound Impedance

**HM100**

Voltage	Operating input current	Standby current	Operating temperature range	Low Frequency range	High Frequency range	Output voltage	Output Power
9V to 15V	12A maximum	0.015A nominal	-30°C to +65°C	182 to 400Hz	500 to 1600Hz	30V	100W

81

#### Features:

- Input voltage 9VDC to 15VDC
- Operating input current 12A maximum
- Polarity Negative-grounded systems only
- Standby current 0.015A nominal
- Operating temperature range -30°C to +65°C
- Low-Frequency range 182 to 400Hz
- High-Frequency range 500 to 1600Hz
- Output voltage 30V
- Output Power 100W
- Dimensions 2.4"(60mm)x6.2"(158mm)Lx5.8"(147mm)

#### Instruction:

- Diameter 15.7cm X 17cm X 21.5cm Height



12V 120-130 6Ω  
Voltage Sound Impedance

**S60**

#### Features:

- Police motorcycle siren and speaker
- 1. 60W speaker(6 ohm), DC12V
- 2. High-quality Aluminum alloy
- 3. Dimensions: 136\*110\*111mm
- 4. Set in one package: 10



Voltage	Sound	Max Power	Output	Impedance	Accessories	Tone
12V	120-130dB	60W	/	60hm	/	3

82



**12V**  
Voltage

**120-130**  
Sound

**11Ω**  
Impedance

## CJB-100PN

Voltage	Sound	Max Power	Output	Impedance	Accessories	Tone
DC 12V	120-130dB	100W	9 outputs	11Ω	Aluminum bracket Fuse Wires	wail, yelp, phaser, horns and mechanical tones

83

### Features:

- All-in-one, multi-function police siren
- The control panel features backlit LED buttons
- 12 VDC
- 100 Watt siren
- Connects by serial port with 15 feet of cable included
- 20 backlit buttons
- Built-in MicroChip processor
- 9 pre-fused switches
- 1 individual fuse system
- 11 Ohms
- 3 user programmable memory buttons
- 135 stickers for easy labeling
- Aluminum bracket
- Wail, Yelp, Phaser, Mechanical, Horn siren sounds
- Built-in PA system
- Compatible with 100-watt siren speakers
- Keypad Dimensions: 6" L X 3" W X .75" H
- Amplifier Dimensions: 7.5" L X 5.75" W X 2.25" H



**12V**  
Voltage

**120-130**  
Sound

**8Ω/11Ω**  
Impedance

## CJB-100DT

Voltage	Sound	Max Power	Output	Impedance	Accessories	Tone
12V	120-130dB	100W	2 output group Each MAX 8A	8Ω, 11Ω	Bracket Fuse Wires	12 tones

### Features:

- 1. It conform to national standrad GB8108-1999.
- 2. Special super-thin design, harmonious with inner decoration. The case is all metal PAINTED black enamel.
- 3. Adjustable metal chrome plated swing bracket, provided.
- 4. Novelty structure, attractive design, excellent performance, complete function, convenient operation.
- 5. Monolithic Integrated circuit in steadier performance.
- 6. The volume of the amplifier tone and warning tone are adjusted as your option.
- 7. With two light controllers.
- 8. 12 tones (Yelp, Horn, Siren, Phsr, Hilo, Wail.....)
- 9. Press the middle round button, it will call up the other 6 tones



84



12/24      120-130      8Ω/11Ω  
 Voltage      Sound      Impedance


**CJB**  
**-100AD**

Voltage	Sound	Max Power	Output	Impedance
12/24V	120-130dB	100W	2 output group Each MAX 8A	8Ω/11Ω

Accessories  
Bracket  
Fuse  
Wires

Tone  
Siren,manual  
wall,yelp,hi-lo  
horn,radio

85



12/24      120-130      8Ω/11Ω  
 Voltage      Sound      Impedance

**CJB**  
**-100CD**

Voltage	Sound	Max Power	Output	Impedance
12/24V	120-130dB	100W	2 output group Each MAX 8A	8Ω/11Ω

Accessories  
Bracket,Fuse  
Wires

Tone  
Siren, wail-2, tool,  
yelp, hi-lo, wail-1, horn

86



Features:

- It conform to national standrad GB8108-1999.
- Special super-thin design, harmonious with inner decoration.
- Case is all metal PAINTED black enamel.
- Adjustable metal chrome plated swing bracket, provided.
- Novelty structure, attractive design, excellent,
- excellent performance, complete function, convenient operation.
- Monolithic Integrated circuit in steadier performance.
- Volume of amplifier tone and warning tone are adjusted are your option.
- With two light controllers.



**12/24**  
Voltage


**116-118**  
Sound

**8Ω/11Ω**  
Impedance

#### Features:

- Meet SAE J1849 and CA Title 13 requirements
- Handhold controller
- Monolithic integrated circuit in steadier performance
- 3 light control buttons
- Dimensions: 7.8" L x 4.3" W x 1.9" H
- Tone: Yelp, wail-1, wail-2, HI-LO, Whistel tone, Wrecker, Radio
- Unique and scientific design, perfect function,
- Convenience for operation, safely and reliably
- Design and produced in accordance with GB standard character

#### Instruction:



**10-14**  
Voltage

**120-130**  
Sound

**4Ω**  
impedance

#### Features:

- Meet GB 8108-1999 «electronic siren for vehicle»
- Remote controller
- Pretty appearance,advanced structure and complete function
- Dimensions: AMP: 225 x 108 x 51mm;
- Controller: 105 x 53 x 19mm
- Siren is exothermic, should be install at a ventilated place
- Controller should be put at a place that easy for user
- to pick up and away from air bag restraint system





 12V  
Voltage

 120-130  
Sound

 4/6/8/11  
Impedance

**Features:**

- 100W speaker
- High-quality Aluminum alloy
- Set in one package: 10
- Impedance: 4/6/8/11ohm
- Material: Aluminum, ABS or PA66 housing, etc.


**S22**  
**Z22**

	Voltage	Sound	Max Power	Impedance	Frequency	Distortion	Dimensions	
S22	12V	120-130dB	100W	4/6/8/11ohm	400-4000Hz	/	171.5*171.5*84mm 165*165*73mm	89


 12V  
Voltage

 120-130  
Sound

 8Ω/11Ω  
Impedance

**Features:**

- 100W speaker
- Black ABS plastic shell and High quality Aluminum alloy
- Dimensions: 18.8\*16.2\*8.7mm
- Set in one package : 6


**SK02**

Voltage	Sound	Max Power	Impedance	Frequency	Distortion	Dimensions	
12V	120-130dB	100W	8Ω/11Ω	400-4000Hz	/	18.8*16.2*8.7mm	90



12V  
Voltage

120-130  
Sound

8Ω/11Ω  
Impedance

**SK03**

Voltage	Sound	Max Power	Impedance	Frequency	Material	Dimensions
12V	120-130dB	100W	8Ω/11Ω	400-4000Hz	Aluminum	/

Features:

- 100W speaker
- ABS plastic shell and High quality Aluminum alloy
- Set in one package : 6
- Impedance: 4/6/11ohm



**S801 80W Speaker**



**S802 80W Speaker**



**S2001 200W Speaker**



**S2002 200W Speaker**



**S20012 200W Speaker**



**SK3C 100W Speaker**

**Speaker**

	Voltage	Sound	Max Power	Impedance	Frequency	Distortion	Dimensions
S801	12V	120-130dB	80W	16Ω	400-4000Hz	/	/
S802	12V	120-130dB	80W	16Ω	400-4000Hz	/	/
S2001	12V	120-130dB	200W	4Ω	400-4000Hz	/	/
S2002	12V	120-130dB	200W	4Ω	400-4000Hz	/	/
S20012	12V	118-125dB	200W	4Ω	300-5000Hz	/	/
SK3C	12V	120-130dB	100W	8Ω/11Ω	400-4000Hz	/	145*125*52mm


**S30 30W Speaker**

**C12 100W Speaker**

**B12 100W Speaker**

**A2 100W Speaker**

**B100 100W Speaker**

**SK06 100W Speaker**

**12V/24V**  
Voltage

**Flood  
Spot LED**  
Lamp type

**Mechanical  
Pneumatic**  
Lifting mode


**Features:**

- System Rated voltage: DC12V/24V
- Lamps Rated voltage: DC12V/24V/AC220V
- Lamp Type: Flood/Spot LED
- Lamp power: 120W\*4
- Rotational speed: 4r/min
- Light lumen: 57600lm
- Total Height: 1.8meter mast
- Lifting mode: Mechanical + Pneumatic
- Horizontal rotary: 380°
- Vertical Rotary: 330°
- With light and system controller of wired & remote
- External spring wires


**Speaker**

	Voltage	Sound	Max Power	Impedance	Frequency	Distortion	Dimensions
S30	12V	120-130dB	30W	17Ω	400-4000Hz	/	/
C12	12V	115-122dB	100W	8Ω/11Ω	400-4000Hz	/	/
B12	12V	115-122dB	100W	8Ω/11Ω	400-4000Hz	/	/
A2	12V	120-130dB	100W	8Ω/11Ω	400-4000Hz	/	/
B100	12V	120-130dB	100W	4/6/8/11ohm	400-4000Hz	/	/
SK06	12V	120-130dB	100W	4/6/8/11ohm	400-4000Hz	/	/

Voltage	Lamp type	Rotational speed	Light lumen	Total Height
12V/24V	Flood/Spot LED	4r/min	57600lm	1.8meter mast


**12/24**  
Voltage

**25**  
Flash Patterns

**IP65**  
Waterproof

Color:

Features:

- Reliable, solid-state, two-output LED flasher
- 25 flash patterns in total
- Insulating paint electronics provide reliable operation and protection against moisture.
- Waterproof: IP65
- Excellent for applications requiring exterior mounting.
- There are two outputs with heavy-duty Amperage making it ideal for multi-light systems.
- Use terminals instead of wires to simplify wiring connections.
- Standard 12V DC, DC 24V for optional choice.
- Surface mounts with screws (provided).
- Dimension: 2.24" D x 6.3" L.
- It can control LED modules without the program.

Dimension:

- 2.24" D x 6.3" L


**Hard wired  
or 9V battery**  
Battery

**45°**  
Activated Angle


**IP67**  
Waterproof

Color:

Features:

- Brand new tail lift safety warning light.
- Gravity configuration IC realizes the main function design
- Synchronous flash
- LED power: 4W, 4PCS\*1W LED
- Battery: Hard wired or 9V battery(10H)(Replacement)
- Beam color: Amber
- Activation Angle: 45°
- Waterproof: IP67
- Material: PC lens, Aluminum housing
- Plating treatment, ultra-thin,
- Install directly with tapping screws without drilling

Dimension:





**100-240**  
Voltage

**9**  
Flash Patterns

**IP67**  
Waterproof

Color:  


Features:

- 6-pack suitcase rechargeable type road flares
- Built-in 9 selectable flash patterns (Rotate/Quad/Single blink/Alternating blinks/SOS rescue/Steady on high/Steady on dim/2 LED flashlight/4 LED flashlight)
- Powered by DC 12V charging cigar plug or 100-240V AC/DC charging adapter
- Single color available(Yellow/Green/Blue/White/Orange/Red)
- Pattern Memory available
- Anti-crushing, waterproof, dustproof, corrosion-resistant
- The yellow light has strong penetrating power in the fog
- Using 053048 rechargeable lithium-ion battery, it can be charged and discharged more than 1,000 times, and can be used for 150 hours after one full charge.

Dimension:

- Flare: 4.25" L X 4.375" W X 1.375" H
- Kit case: 17.5" L X14.5" W X 2.5" H



**12-24**  
Voltage

**/**  
Flash Patterns

**IP67**  
Waterproof

Color:  


Features:

- 4 Inch Round Chrome plated Tail Light
- Truck and trailer LED lighting with STT(stop/turn/tail) functions
- Flash function available
- Powered by DC 12-24V
- 14Pcs+16Pcs 0.4W LEDs
- Amber/Red/White lens available
- IP67 Waterproof PC Lens, Shock Proof, Dust Proof
- Easy to install in all locations
- Test Each Item and 100% Ensure In Good Condition Before Shipped
- 5 wires(Red: Halo+Middle Part; Blue: Middle Part; White: Halo; Yellow: Flash; Black: GND)

Dimension:





**3.7**  
Voltage

1 flash with  
white steady on

**IP67**  
Waterproof

**JZ08**  
shoulder light

Voltage  
3.7V

LED Power  
0.25W 8PCS

Frequency  
8 Hz

Installation  
Clip

Visible Distance  
500m

Color:



Features:

- The key is to press the 2-second button into the scintillation model: then click the button, enter the small flashing light mode, then each press the key switch back and forth flash mode and small flashing light mode, key long press 2 seconds equipment shut down.
- Shoulder lights without long-term use should be filled with 50%-80% power. Store the product in a cool, dry environment, and recharge the battery every 3 months to avoid battery self-discharge caused by power being too low during long-term storage, which can cause irreversible capacity loss.
- Self-discharge is influenced by environment and humidity for lithium batteries high temperature and moisture will accelerate battery self-discharge, so it should be stored in a dry environment with battery 0°C-20°C

Dimension:

- 79.5\*40\*33.5mm



## SPECIFICATIONS

### Description



Item	CT6	EG6	N6	G3	KL6	Z12
LED Power	3W LEDs	3W LEDs	3W LEDs	3PCS 3W	3W LEDs	3W LEDs
Lens	/	Fresnel	Fresnel	TIR	TIR	/
LED Lifespan	100000H	100000H	100000H	100000H	100000H	100000H
Flash pattern	20/25	12	19	14	16/10	16/10
Input voltage	10-33V	10-33V	12-24V	12V	10-30V	12-24V
Max Power	18W	18W	18W	9W	18W	36W
Colour Available	single or dual or trio	single or dual or trio	single or dual or trio	single	single or dual	single or dual
Ambient temperature	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C
Waterproof	IP67	IP67	IP67	IP67	IP67	IP67
Product Dimension	105mm L x 28mm W x 12mm H	118mm L x 25mm W x 7mm H	126mm L x 27mm W x 21mm H	86.4mm L x 25.4mm W x 26.7mm H	108mm L x 27mm W x 22mm H	136mm L x 43.2mm W x 11.5mm H
Mounting	Surface mount	surface mount/L-bracket /3M/hood mount	Surface mount	Surface mount	Hood mount	Surface mount
Certifications	ECE R65, SAE	ECE R65, SAE	ECE R65	/	/	ECE R65 XA1
Wire	4 core	5 core	4 core or 5 core	3 core	4 core	4 core
Cable length	20cm	20cm	20cm	20cm	20cm	20cm
Material	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC

# SPECIFICATIONS

Description				
Item	<b>NT6</b>	<b>M3/M4/M6</b>	<b>M12</b>	<b>TS-series</b>
LED Power	6/12Pcs 3W LEDs	3/4/6PCS 3W	12PCS 3W	3W CREE or Osram LEDs
Lens	/	TIR	TIR	Fresnel lens
LED Lifespan	100000H	100000H	100000H	100000H
Flash pattern	12	16	16	19
Input voltage	10-30V	12-24V	12-24V	12-24V
Max Power	18W	9/12/18W	36W	/
Colour Available	Single and Dual color	Single or Split	Single or Split	Single or Split color
Ambient temperature	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C
Waterproof	IP67	IP67	IP67	IP67
Product Dimension	120mm L x 15.8mm W x 22.2mm H	86.2/96.1/124.1mm L x 34.4mm W x 20.5mm H	121mm L x 47.4mm W x 14.5mm H	/
Mounting	Surface mount, L-bracket mount, Stud mount	Surface mount	Surface mount	Surface mount 3M mount
Certifications	ECE R65	/	/	ECE R65, R10 and SAE
Wire	4 core	5 core	5 core	4 core
Cable length	20cm	20cm	20cm	20cm
Material	Aluminum base, UV-resistant PC	Aluminum alloy base	Aluminum alloy base	Aluminum alloy base, UV-resistant PC

			
<b>V-series</b>	<b>WS06</b>	<b>H6</b>	<b>Q4</b>
3W CREE LEDs	3W LEDs	6Pcs or 12Pcs 3W	4pcs 3W LEDs and 4pcs 0.5W white LEDs
TIR	TIR	Linear	Fresnel
100000H	100000H	100000H	100000H
18	19	19 or 12	19
12-24V	10-33V	10-33V	12-24V
9/12/18W	18W	18W	12W
single or split color	single	Single or Split or Dual color	single color
-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C
IP67	IP69K	IP67	IP67
V3: 114*30*9mm V4: 141*30*9mm V6: 196*30*9mm	179.7 mmL x 60.9 mmW x 28 mmH	124 mmL x 25 mmW x 30 mmH	57 mmL x 45 mmW x 11 mmH
Surface mount 3M mount	Surface mount	Hood and L mount	Surface mount 3M mount
ECE R65, R10 SAE Class1	ECE R10,R65 Class2 SAE J595 Class1, R148	/	ECE R65, R10 and SAE
4 core	5 core	4 core	5 core
20cm	20cm	25cm	20cm
UV-resistant PC lens, and PP material	Aluminum alloy base, UV-resistant PC	Aluminum alloy base, UV-resistant PC	UV-resistant PC lens PP material

# SPECIFICATIONS


Description				
Item	<b>Marv</b>	<b>SKL</b>	<b>Matrix</b>	<b>Mavic</b>
LED Power	3W LEDs	3W LEDs	3W LEDs	3W LEDs
Lens	/	/	Red/Blue/Clear/Amber	Blue/Clear/Amber
LED Lifespan	100000H	100000H	100000H	100000H
Flash pattern	31	25	16	16
Input voltage	12V or 12-24V	12V	10-30V	10-30V
Max Power	/	/	/	/
Colour Available	single or split color	single and split	single or dual or trio color	single or dual
Ambient temperatur	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C
Waterproof	IP67	IP67	IP67	IP67
Product Dimension	18"/27"/36"/48"/55" L*11.4" W *3.4" H (with feet)	24"/30"/42"/47"/59"/72" L * 11" W * 4" H (include feet)	(690-2050)mm L x 300mm W x 136mm H	(740-2090)mm L x 240mm W x 138mm H
Mounting	Magnet mount or Gutter Mount	Gutter Mount	Magnet mount or Gutter Mount	Magnet mount or Gutter Mount
Certifications	/	/	ECE R65 TA1,TB1, ECE R10	ECE R65 TA1,TB1, ECE R10
Wire	/	/	/	/
Cable length	4m of cable with controller provided	4m of cable with controller provided	4m of cable with controller provided	4m of cable with controller provided
Material	Black aluminum top housing, UV-resistant PC	Aluminum top housing, UV-resistant PC	UV-resistant PC	UV-resistant PC

				
<b>NRO</b>	<b>NEO</b>	<b>Matrix mini</b>	<b>ET30/ET60</b>	<b>M108</b>
3W LEDs	3W LEDs	40pcs 3W	30/60PCS 3W	108Pcs 0.3W
TIR	TIR	TIR	/	/
100000H	100000H	100000H	100000H	100000H
31	16	15	12	15
12V or 12-24V	10-30V	10-30V	12-30V	12-24V
/	/	120W	90W/180W	30W
single, split color, dual color	single, split and dual color	single or dual or trio color	single or split	Amber
-40°C~65°C	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C
IP67	IP67	IP67	IP67	IP67
13/23/33/43/53 inch(L) X 4.85"(W) X 0.98"(H)	(700-1930)mm L X 220mm W X 100mm H	590mm L x 300mm W x 136mm H	305mm L x 185mm W x 45mm H	420mm L x 207mm W x 149mm H
Gutter Mount or Magnet Mount	Magnet mount or Gutter Mount	Magnet mount	Magnet mount,Or Screw	Magnet mount
/	Pending	ECE R65 TA1,TB1, ECE R10	/	/
/	/	/	/	/
4m of cable with cigar plug provided	4m of cable with controller provided	4m of cable with controller provided	2.8m of cable with cigarette plug provided	3m of cable with cigarette plug provided
Aluminum top housing, UV-resistant PC	UV-resistant PC	UV-resistant PC	UV-resistant PC	UV-resistant PC

# SPECIFICATIONS

Description					
Item	<b>PC12/PC18</b>	<b>PC8</b>	<b>PL8</b>	<b>PC16</b>	<b>PL16</b>
LED Power	12/18PCS 5W	8PCS 3W	8PCS 3W	16PCS 3W	16PCS 3W
Lens	Clear	Amber/Red/Clear/Blue	Clear/Amber/Red/Blue	Amber/Red/Clear/Blue	Amber/Red/Clear/Blue
LED Lifespan	100000H	100000H	100000H	100000H	100000H
Flash pattern	37	18	18	18	18
Input voltage	12-24V	DC12V or DC24V	DC12V or DC24V	DC12V or DC24V	DC12V or DC24V
Max Power	60W/90W	24W	24W	48W	48W
Colour Available	Single or dual color	Single color or split	single or split color	Single color or split	Single color or split
Ambient temperature	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C
Waterproof	IP67	IP67	IP67	IP67	IP67
Product Dimension	PC12: 20.3 x 9.5 x 2.5cm PC18: 17.9 x 12 x 2.5cm	201mm L x 94mm W x 40mm H	17.6mm L x 11.5mm W x 4.6mm H	268mm L x 212mm W x 55mm H	242mm L x 184mm W x 50mm H
Mounting	Surface mount	Surface mount	Surface mount	Surface mount	Surface mount
Certifications	/	/	/	/	/
Wire	8 core	3 core	4 core or 3 core	3 core	3 core
Cable length	20cm	20cm	20cm	20cm	20cm
Material	Aluminum alloy base, UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC	Aluminum alloy base UV-resistant PC

				
<b>U1200</b>	<b>DF12</b>	<b>DX12</b>	<b>VN48</b>	<b>VL10</b>
12PCS 3W	12PCS 3W	12PCS 5W	48PCS 3W	3W LEDs
/	TIR	Fresnel	Fresnel	Linear
100000H	100000H	100000H	100000H	100000H
19	16	35	41	32
10-30V	12V	10-30V	12V	12V
36W	36W	60W	144W	/
Single or dual color	single or dual color	single or split	single or split or dual color	single or split or dual
-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C	-30--+70°C
IP67	/	/	/	/
ø 36mm x 20mm H	263 mmL x 88 mmW x 28 mmH	320mmL x 100mmW x 55mmH	Half:450mm L x 105mm W x 30mm H	Half: 522mm Lx 150mm x 90mm x 26mm H
Surface mount	Suction cup mount	Suction cup mount	Brackets mount	Brackets mount
/	/	/	/	/
4 core	/	4 core	/	/
20CM	3m of cable with cigarette plug provided	3m of cable with cigarette plug provided	3m of cable with cigarette plug provided	3m of cable with default controller or hard wired
Aluminum alloy base UV-resistant PC	Aluminum alloy base, UV-resistant PC	Aluminum housing, Lens PMMA	Aluminum alloy	Aluminum alloy base UV-resistant PC



#### WHAT MAKES US UNIQUE

UNIT SIGNAL was established in 2014. We are the manufacturer of Public Safety Warning Products and Systems for emergency services. We believe that the first responders should have the best products and the best technology to ensure the safety of workers, first responders, and our community.

#### Design & Engineering

UNIT SIGNAL believes that the key to continued growth and success is through continuous product development, combined with excellent customer service, low delivery times, competitive prices, and product reliability. We can custom design and manufacture LED warning lights according to customer specifications and other requirements.

#### Electronics Manufacturing

One-stop electronic manufacturing: purchase of components, the supply of circuit substrates, design and application of built-in electronic equipment, manufacturing, assembly, and testing. We provide a full range of quality control and technical services.

#### Quality Control & Testing

We use an intelligent production system to monitor all production links in real-time, and do strict quality control testing, which greatly improves production efficiency and shortens the delivery time.

#### Delivery Policy

If the product is in stock, it can usually be shipped within 24 hours, small orders are usually shipped within 5-7 days. We try our best to provide customers with an experience beyond expectations, and usually send orders before the forecast date to ensure customer satisfaction.

#### Customer Service

We stand behind all our products and offer a 2-5 years warranty on our merchandise, which is provided directly by us. We test all our products in real environments and industry-standard testing facilities. Customer satisfaction has always been our top priority. Each of our customers will receive the greatest care and respect. Our customers make us.

#### Best selection

Focus on providing the best solution at the best price. We strive to make UNIT SIGNAL your first choice in the market.

Unit Signal dedicates to achieve mutual development and concentrates on supplying reliable, beautifully-crafted, well-functioned and economical LED warning lights.

we are always looking for new partners to help our products reach the customers and we are committed to creating and delivering the latest and greatest products that fulfills the needs of our customers.

**INNOVATION - EXCELLENCE - TRUST**